



ELEMENT 999 RSL

CRS527 / CFS527 (frame only)



TECHNOLOGY



IMPROVEMENTS

Full 2x11 Shimano Di2 Electronic Shifting: Precise, Wide Range Gearing.

Stan's Valor Carbon Wheels: 1250g and Increased Stiffness.

Full Fox Factory Kashima Suspension: Supple, Reliable Performance.

GEOMETRY

| FRAME SIZE | | SM | MD | LG | XL | XXL |
|------------------------------|---------|-------|-------|-------|-------|-------|
| HEAD ANGLE | degrees | 70.6° | 70.6° | 70.6° | 70.6° | 70.6° |
| SEAT ANGLE | degrees | 74° | 74° | 74° | 74° | 74° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 394 | 432 | 470 | 508 | 546 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 558 | 582 | 605 | 630 | 655 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 445 | 445 | 445 | 445 | 445 |
| BOTTOM BRACKET DROP | (mm) | 40 | 40 | 40 | 40 | 40 |
| STANDOVER HEIGHT | (mm) | 771 | 771 | 771 | 771 | 771 |
| WHEELBASE | (mm) | 1066 | 1097 | 1120 | 1146 | 1172 |
| REACH | (mm) | 388 | 409 | 429 | 452 | 473 |
| STACK | (mm) | 592 | 603 | 612 | 622 | 636 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | SMOOTHWALL™ Carbon. ABC™ Pivots. Tapered Head Tube. Press Fit BB. |
| COLOR | Matte Carbon |
| SIZE | S - M - L - XL - XXL |
| SHOCK | Fox Float Remote CTD Kashima Custom Race Valved. SmoothLink™ Design 95mm. Rebound / Remote Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings |
| FORK | Fox 32 Float 29 100 FIT CTD Adjust Kashima. 100mm. FIT Damper / Rebound / Climb (Lockout) - Trail (3 Position Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer |
| HEADSET | Cane Creek Forty Series: IS42mm Top / 52mm Bottom Tapered |
| BRAKE LEVERS | Shimano XTR I-Spec II Shifter Mount |
| BRAKES | Shimano XTR Hydraulic Disc 180mm |
| CASSETTE | Shimano XTR 11-40T 11spd |
| CHAIN | Shimano XTR Sil-Tec 11spd |
| CRANKS | Shimano XTR 170-175mm 38/28T 2x11spd |
| BOTTOM BRACKET | Shimano XTR Press Fit |
| SHIFTERS | Shimano XTR Switch Shift Di2 I-Spec II 2x11spd |
| F. DERAILLEUR | Shimano XTR Di2 E Mount 2x11spd |
| R. DERAILLEUR | Shimano XTR Di2 Shadow Plus Direct Mount 11spd |
| F. HUB | Stan's 3.30Ti Hub / 24H / 15mm Axle |
| R.HUB | Stan's 3.30Ti Hub / 28H / Alloy Freehub / 12 x 142mm Axle |
| SPOKES | Sapim Laser |
| RIMS | Stan's Valor Carbon Tubeless Ready |
| TIRES | Maxxis Ikon Maxx Speed Folding Tubeless Ready 29" x 2.2" |
| HANDLEBAR | Race Face Next 1/2 Rise Ø35mm x 740mm x 9° Sweep |
| STEM | Race Face Turbine CNC 35mm 6° x 70-90mm |
| GRIPS | ESI Silicone Super Light |
| SADDLE | WTB Silverado SLT Titanium |
| SEATPOST | Race Face Next SL Carbon 30.9mm x 400mm |

*Price, specification and availability subject to change without notice.



ELEMENT 970 RSL

CRS524



TECHNOLOGY



IMPROVEMENTS

Race Face Turbine Cinch 30mm Crank: Lighter and Stiffer.

Shimano XTR Shadow Plus Rear Derailleur for Chain Management.

Race Face 35mm Bar / Stem: Lighter and Stiffer and Wider.

GEOMETRY

| FRAME SIZE | | SM | MD | LG | XL | XXL |
|------------------------------|---------|-------|-------|-------|-------|-------|
| HEAD ANGLE | degrees | 70.6° | 70.6° | 70.6° | 70.6° | 70.6° |
| SEAT ANGLE | degrees | 74° | 74° | 74° | 74° | 74° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 394 | 432 | 470 | 508 | 546 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 558 | 582 | 605 | 630 | 655 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 445 | 445 | 445 | 445 | 445 |
| BOTTOM BRACKET DROP | (mm) | 40 | 40 | 40 | 40 | 40 |
| STANDOVER HEIGHT | (mm) | 771 | 771 | 771 | 771 | 771 |
| WHEELBASE | (mm) | 1066 | 1097 | 1120 | 1146 | 1172 |
| REACH | (mm) | 388 | 409 | 429 | 452 | 473 |
| STACK | (mm) | 592 | 603 | 612 | 622 | 636 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | SMOOTHWALL™ Carbon. ABC™ Pivots. Tapered Head Tube. Press Fit BB. |
| COLOR | Gloss Neon Red |
| SIZE | S - M - L - XL - XXL |
| SHOCK | Fox Float Remote CTD Custom Race Valved. SmoothLink™ Design 95mm. Rebound / Remote Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings |
| FORK | Fox 32 Float 29 100 FIT CTD. 100mm. FIT Damper / Rebound / Climb (Lockout) - Trail (Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer |
| HEADSET | Cane Creek Forty Series: 1542mm Top / 52mm Bottom Tapered |
| BRAKE LEVERS | Shimano XT I-Spec Shifter Mount |
| BRAKES | Shimano XT Hydraulic Disc 180mm |
| CASSETTE | Shimano HG81 11-36T 10spd |
| CHAIN | Shimano HG95 10spd |
| CRANKS | Race Face Turbine Cinch 170-175mm 38/24T 2x10spd |
| BOTTOM BRACKET | Race Face Cinch 30mm BB92 Press Fit |
| SHIFTERS | Shimano XT Rapid Fire I- Spec 2x10spd |
| F. DERAILLEUR | Shimano XT E Mount 2x10spd |
| R. DERAILLEUR | Shimano XTR Shadow Plus Direct Mount 10spd |
| F. HUB | Shimano XT / Centerlock / 32H / 15mm Axle |
| R.HUB | Shimano XT / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Stan's ZTR Crest Tubeless Ready |
| TIRES | Maxxis Ikon Folding 29" x 2.2" |
| HANDLEBAR | Race Face Turbine 1/2 Riser 035mm x 740mm x 9° Sweep |
| STEM | Race Face Turbine 35mm 6° x 70-90mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Silverado Race |
| SEATPOST | Race Face Turbine 30.9mm x 400mm |

*Price, specification and availability subject to change without notice.



ELEMENT 950 RSL

CRS518



TECHNOLOGY



IMPROVEMENTS

Manitou Marvel Pro Fork: Supple ISO Air Spring and TPC Damping

Shimano XT Brakes, Shifter and Front Derailleur: The Benchmark for Reliable Performance

Shimano XT Shadow Plus Rear Derailleur for Chain Management.

GEOMETRY

| FRAME SIZE | | SM | MD | LG | XL | XXL |
|------------------------------|---------|-------|-------|-------|-------|-------|
| HEAD ANGLE | degrees | 70.6° | 70.6° | 70.6° | 70.6° | 70.6° |
| SEAT ANGLE | degrees | 74° | 74° | 74° | 74° | 74° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 394 | 432 | 470 | 508 | 546 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 558 | 582 | 605 | 630 | 655 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 445 | 445 | 445 | 445 | 445 |
| BOTTOM BRACKET DROP | (mm) | 40 | 40 | 40 | 40 | 40 |
| STANDOVER HEIGHT | (mm) | 771 | 771 | 771 | 771 | 771 |
| WHEELBASE | (mm) | 1066 | 1097 | 1120 | 1146 | 1172 |
| REACH | (mm) | 388 | 409 | 429 | 452 | 473 |
| STACK | (mm) | 592 | 603 | 612 | 622 | 636 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | SMOOTHWALL™ Carbon. ABC™ Pivots. Tapered Head Tube. Press Fit BB. |
| COLOR | Matte Green |
| SIZE | S - M - L - XL - XXL |
| SHOCK | Fox Float Remote CTD Custom Race Valved. SmoothLink™ Design 95mm. Rebound / Remote Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings |
| FORK | Manitou Marvel Pro. 100mm. TPC Absolute+ Damper / Compression / Lockout / Rebound / 15mm HexLock Axle / Tapered Steerer |
| HEADSET | Cane Creek Fifteen Series: 1542mm Top / 52mm Bottom Tapered |
| BRAKE LEVERS | Shimano XT I-Spec Shifter Mount |
| BRAKES | Shimano XT Hydraulic Disc 180mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | Race Face Turbine 170-175mm 38/24T 2x10spd |
| BOTTOM BRACKET | Race Face Press Fit Team XC |
| SHIFTERS | Shimano XT Rapid Fire I-Spec 2x10spd |
| F. DERAILLEUR | Shimano XT E Mount 2x10spd |
| R. DERAILLEUR | Shimano XT Shadow Plus Direct Mount 10spd |
| F. HUB | Shimano 618 / Centerlock / 32H / 15mm Axle |
| R.HUB | Shimano 618 / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Wheeltech Inferno 23 by SUNringlé |
| TIRES | Maxxis Ikon Folding 29" x 2.2" |
| HANDLEBAR | Race Face Evolve Flat Wide Ø31.8mm x 720mm x 9° Sweep |
| STEM | Race Face 6° x 70-100mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Volt Race |
| SEATPOST | Rocky Mountain XC 30.9mm x 400mm |

*Price, specification and availability subject to change without notice.



THUNDERBOLT 799 MSL

CRF527 / CFF527 (frame only)



TECHNOLOGY



GEOMETRY

| FRAME SIZE | | XS | SM | MD | LG | XL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 67.2° - 68.4° | 67.2° - 68.4° | 67.2° - 68.4° | 67.2° - 68.4° | 67.2° - 68.4° |
| SEAT ANGLE | degrees | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 381 | 419 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 540 | 565 | 590 | 615 | 645 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 426 | 426 | 426 | 426 | 426 |
| BOTTOM BRACKET DROP | (mm) | 25.2 - 4.7 | 25.2 - 4.7 | 25.2 - 4.7 | 25.2 - 4.7 | 25.2 - 4.7 |
| STANDOVER HEIGHT | (mm) | 715 | 715 | 715 | 715 | 715 |
| WHEELBASE | (mm) | 1,072 | 1,098 | 1,124 | 1,150 | 1,181 |
| REACH | (mm) | 376 - 393 | 398 - 415 | 420 - 437 | 443 - 460 | 469 - 486 |
| STACK | (mm) | 544 - 552 | 553 - 561 | 562 - 570 | 572 - 580 | 586 - 594 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | SMOOTHWALL™ Carbon. PipeLock™ Main Pivot + BC2™ & ABC™ Bushings. Tapered Head Tube. Press Fit BB. RIDE-9™ Adjustable Geometry & Suspension Rate. Di2 Ready. |
| COLOR | Matte Green Carbon |
| SIZE | XS - S - M - L - XL |
| SHOCK | Fox Float CTD Remote Kashima Custom Trail Valved. SmoothLink™ Design 120mm. Rebound / Remote Climb (X-Firm ProPedal) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate |
| FORK | Fox 32 Float 27.5 120 FIT CTD Adjust Kashima. 120mm. FIT Damper / Rebound / Climb (Lockout) - Trail (3 Position Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer |
| HEADSET | Cane Creek Forty Series: IS42mm Top / IS52mm Bottom Tapered |
| BRAKE LEVERS | Shimano XTR I-Spec II Shifter Mount |
| BRAKES | Shimano XTR Hydraulic Disc 180mm |
| CASSETTE | Shimano XTR 11-40T 11spd |
| CHAIN | Shimano XTR SiL-Tec 11spd |
| CRANKS | Shimano XTR 170-175mm 38/28T 2x11spd |
| BOTTOM BRACKET | Shimano XTR Press Fit |
| SHIFTERS | Shimano XTR Switch Shift Di2 I-Spec II 2x11spd |
| F. DERAILLEUR | Shimano XTR Di2 E Mount 2x11spd |
| R. DERAILLEUR | Shimano XTR Di2 Shadow Plus Direct Mount 11spd |
| F. HUB | Stan's 3.30Ti Hub / 24H / 15mm Axle |
| R.HUB | Stan's 3.30Ti Hub / 28H / Alloy Freehub / 12 x 142mm Axle |
| SPOKES | Sapim Laser |
| RIMS | Stan's Valor Carbon Tubeless Ready |
| TIRES | Maxxis Maxx Speed Tubeless Ready F + R: Ardent Race 27.5" x 2.2" |
| HANDLEBAR | Race Face Next SL Carbon 1/2 Rise Ø35mm x 740mm x 9° Sweep |
| STEM | Race Face Turbine CNC 35mm 6° x 60-80mm |
| GRIPS | ESI Silicone Super Light |
| SADDLE | WTB Silverado Carbon |
| SEATPOST | RockShox Reverb Stealth 30.9mm x 350-420mm |

*Price, specification and availability subject to change without notice.



THUNDERBOLT 790 MSL

CRF519

BC EDITION



TECHNOLOGY



GEOMETRY

| FRAME SIZE | | XS | SM | MD | LG | XL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 66.5° - 68.2° | 66.5° - 73.0° | 66.5° - 73.0° | 66.5° - 73.0° | 66.5° - 68.2° |
| SEAT ANGLE | degrees | 73.0° - 74.6° | 73.0° - 74.6° | 73.0° - 74.6° | 73.0° - 74.6° | 73.0° - 74.6° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 381 | 419 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 540 | 565 | 590 | 615 | 645 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 426 | 426 | 426 | 426 | 426 |
| BOTTOM BRACKET DROP | (mm) | 20.2 - 0.5 | 20.2 - 0.5 | 20.2 - 0.5 | 20.2 - 0.5 | 20.2 - 0.5 |
| STANDOVER HEIGHT | (mm) | 715 | 715 | 715 | 715 | 715 |
| WHEELBASE | (mm) | 1,072 | 1,098 | 1,124 | 1,150 | 1,181 |
| REACH | (mm) | 368 - 385 | 390 - 408 | 413 - 430 | 436 - 452 | 461 - 479 |
| STACK | (mm) | 554 - 562 | 563 - 571 | 572 - 581 | 582 - 590 | 596 - 604 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | SMOOTHWALL™ Carbon. Pipelock™ Main Pivot + BC™ & ABC™ Bushings. Tapered Head Tube. Press Fit BB. RIDE-9™ Adjustable Geometry & Suspension Rate. Di2 Ready. |
| COLOR | Matte Dark Blue |
| SIZE | XS - S - M - L - XL |
| SHOCK | RockShox Monarch RT3 Custom BC Valved. SmoothLink™ Design 120mm. Rebound / 3 Position Compression / Adjustable Suspension Rate |
| FORK | RockShox Pike RCT3 27.5. 130mm. Charger Damper / Rebound / Adjustable 3 Position Compression / 15mm Axle / Tapered Steerer |
| HEADSET | Cane Creek Forty Series: IS42mm Top / 52mm Bottom Tapered |
| BRAKE LEVERS | Shimano XT |
| BRAKES | Shimano XT Ice-Tec Hydraulic Disc 180mm |
| CASSETTE | Sram XG-1195 10-42T 11spd |
| CHAIN | Sram PC-XX1 11spd |
| CRANKS | Race Face Turbine Cinch 170-175mm 32T Direct Mount 1x11spd |
| BOTTOM BRACKET | Race Face Cinch 30mm BB92 Press Fit |
| SHIFTERS | Sram X01 Trigger 1x11spd |
| F. DERAILLEUR | N/A |
| R. DERAILLEUR | Sram X01 Type 2 All Mountain 11spd |
| F. HUB | Stan's 3.30 Disc / 15mm Axle |
| R.HUB | Stan's 3.30 Disc / 6 Pawl XD Freehub / 142 x 12mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Stan's ZTR Flow Tubeless Ready |
| TIRES | Maxxis Ardent EXO 27.5" x 2.4" |
| HANDLEBAR | Race Face Next SL 1/2 Rise Ø35mm x 760mm x 9° Sweep |
| STEM | Race Face Turbine 35mm 6° x 50-70mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Silverado SLT Titanium |
| SEATPOST | RockShox Reverb Stealth 30.9mm x 350-420mm |

*Price, specification and availability subject to change without notice.



THUNDERBOLT 770 MSL

CRF515



TECHNOLOGY



GEOMETRY

| FRAME SIZE | | XS | SM | MD | LG | XL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 67.2° - 68.4° | 67.2° - 68.4° | 67.2° - 68.4° | 67.2° - 68.4° | 67.2° - 68.4° |
| SEAT ANGLE | degrees | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 381 | 419 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 540 | 565 | 590 | 615 | 645 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 426 | 426 | 426 | 426 | 426 |
| BOTTOM BRACKET DROP | (mm) | 25.2 - 4.7 | 25.2 - 4.7 | 25.2 - 4.7 | 25.2 - 4.7 | 25.2 - 4.7 |
| STANDOVER HEIGHT | (mm) | 715 | 715 | 715 | 715 | 715 |
| WHEELBASE | (mm) | 1,072 | 1,098 | 1,124 | 1,150 | 1,181 |
| REACH | (mm) | 376 - 393 | 398 - 415 | 420 - 437 | 443 - 460 | 469 - 486 |
| STACK | (mm) | 544 - 552 | 553 - 561 | 562 - 570 | 572 - 580 | 586 - 594 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | SMOOTHWALL™ Carbon. Pipelock™ Main Pivot + BC2™ & ABC™ Bushings. Tapered Head Tube. Press Fit BB. RIDE-9™ Adjustable Geometry & Suspension Rate. Di2 Ready. |
| COLOR | Matte Dark Red |
| SIZES | XS - S - M - L - XL |
| SHOCK | Fox Float Remote CTD Custom Race Valved. SmoothLink™ Design 120mm. Rebound / Remote Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate |
| FORK | Fox 32 Float 27.5 120 FIT CTD. 120mm. FIT Damper / Rebound / Climb (Lockout) - Trail (Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer |
| HEADSET | Cane Creek Forty Series: IS42mm Top / 52mm Bottom Tapered |
| BRAKE LEVERS | Shimano XT I-Spec Shifter Mount |
| BRAKES | Shimano XT Hydraulic Disc 180mm |
| CASSETTE | Shimano XT 11-36T 10spd |
| CHAIN | Shimano HG95 10spd |
| CRANKS | Race Face Turbine Cinch 170-175mm 38/24T 2x10spd |
| BOTTOM BRACKET | Race Face Cinch 30mm BB92 Pressfit |
| SHIFTERS | Shimano XT Rapid Fire I-Spec 2x10spd |
| F. DERAILLEUR | Shimano XT E Mount 2x10spd |
| R. DERAILLEUR | Shimano XTR Shadow Plus Direct Mount 10spd |
| F. HUB | Shimano XT / Centerlock / 32H / 15mm Axle |
| R. HUB | Shimano XT / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Stan's ZTR Crest Tubeless Ready |
| TIRES | Maxxis Folding F: Ardent 27.5" x 2.25" R: Ardent Race 27.5" x 2.2" |
| HANDELBAR | Race Face Turbine 1/2 Rise Ø35mm x 740mm x 9° Sweep |
| STEM | Race Face Turbine 35mm 6° x 60-80mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Silverado Race |
| SEATPOST | RockShox Reverb Stealth 30.9mm x 355-420mm |

*Price, specification and availability subject to change without notice.



THUNDERBOLT 750 MSL

CRF512



TECHNOLOGY



GEOMETRY

| FRAME SIZE | | XS | SM | MD | LG | XL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 67.2° - 68.4° | 67.2° - 68.4° | 67.2° - 68.4° | 67.2° - 68.4° | 67.2° - 68.4° |
| SEAT ANGLE | degrees | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 381 | 419 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 540 | 565 | 590 | 615 | 645 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 426 | 426 | 426 | 426 | 426 |
| BOTTOM BRACKET DROP | (mm) | 25.2 - 4.7 | 25.2 - 4.7 | 25.2 - 4.7 | 25.2 - 4.7 | 25.2 - 4.7 |
| STANDOVER HEIGHT | (mm) | 715 | 715 | 715 | 715 | 715 |
| WHEELBASE | (mm) | 1,072 | 1,098 | 1,124 | 1,150 | 1,181 |
| REACH | (mm) | 376 - 393 | 398 - 415 | 420 - 437 | 443 - 460 | 469 - 486 |
| STACK | (mm) | 544 - 552 | 553 - 561 | 562 - 570 | 572 - 580 | 586 - 594 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | SMOOTHWALL™ Carbon. Pipelock™ Main Pivot + BC2™ & ABC™ Bushings. Tapered Head Tube. Press Fit BB. RIDE-9™ Adjustable Geometry & Suspension Rate. Di2 Ready. |
| COLOR | Matte Dark Blue |
| SIZES | XS - S - M - L - XL |
| SHOCK | Fox Float Remote CTD Custom Race Valved. SmoothLink™ Design 120mm. Rebound / Remote Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate |
| FORK | Fox 32 Float 27.5 120 Evolution CTD. 120mm. Rebound / Climb (Lockout) - Trail (Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer |
| HEADSET | Cane Creek Fifteen Series: IS42mm Top / 52mm Bottom Tapered |
| BRAKE LEVERS | Shimano SLX I-Spec Shifter Mount |
| BRAKES | Shimano SLX Hydraulic Disc 180/160mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | Race Face Turbine 170-175mm 38/24T 2x10spd |
| BOTTOM BRACKET | Race Face Team XC Press Fit |
| SHIFTERS | Sram X7 Triggers 2x10spd |
| F. DERAILLEUR | Sram X7 S3 Direct Mount 2x10spd |
| R. DERAILLEUR | Sram X9 Type 2 All Mountain 10spd |
| F. HUB | Shimano SLX / Centerlock / 32H / 15mm Axle |
| R. HUB | Shimano SLX / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Wheeltech Helix TR25 Tubeless Compatible by SUNringlé |
| TIRES | Maxxis Folding F: Ardent 27.5" x 2.25" R: Ardent Race 27.5" x 2.2" |
| HANDELBAR | Race Face Evolve 1/2 Rise Ø31.8mm x 750mm x 9° Sweep |
| STEM | Race Face 6° x 60-80mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Volt Race |
| SEATPOST | X Fusion HiLo Strate 30.9mm x 420mm |

*Price, specification and availability subject to change without notice.



THUNDERBOLT 750

CRF509



TECHNOLOGY



IMPROVEMENTS

Shimano SLX / XT 2x10 Drivetrain: 38/24 for XC Riding.

Shimano XT Shadow Plus Rear Derailleur for Chain Management.

High Performance Maxxis Folding Tires.

GEOMETRY

| FRAME SIZE | | XS | SM | MD | LG | XL |
|------------------------------|---------|-------|-------|-------|-------|-------|
| HEAD ANGLE | degrees | 68.5° | 68.5° | 68.5° | 68.5° | 68.5° |
| SEAT ANGLE | degrees | 74.5° | 74.5° | 74.5° | 74.5° | 74.5° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 381 | 419 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 540 | 565 | 590 | 615 | 645 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 426 | 426 | 426 | 426 | 426 |
| BOTTOM BRACKET DROP | (mm) | 20 | 20 | 20 | 20 | 20 |
| STANDOVER HEIGHT | (mm) | 715 | 715 | 715 | 715 | 715 |
| WHEELBASE | (mm) | 1,072 | 1,098 | 1,124 | 1,150 | 1,181 |
| REACH | (mm) | 381 | 404 | 426 | 449 | 475 |
| STACK | (mm) | 573 | 582 | 591 | 601 | 615 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | FORM™ 7005 Series Custom Hydroformed Alloy, ABC™ Pivots, Tapered Head Tube, Press Fit BB. |
| COLOR | Matte Black |
| SIZES | XS - S - M - L - XL |
| SHOCK | Fox Float CTD Custom Race Valved, SmoothLink™ Design 120mm. Rebound / Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings |
| FORK | Fox 32 Float 27.5 120 CTD, 120mm. Rebound / Climb (Lockout) - Trail (Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer |
| HEADSET | Cane Creek Fifteen Series: Z544mm Top / Z556mm Bottom Tapered |
| BRAKE LEVERS | Shimano SLX I-Spec Shifter Mount |
| BRAKES | Shimano SLX Hydraulic Disc 180/160mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | Race Face Turbine 170-175mm 38/24T 2x10spd |
| BOTTOM BRACKET | Race Face Team XC Press Fit |
| SHIFTERS | Shimano SLX Rapid Fire I-Spec 2x10spd |
| F. DERAILLEUR | Shimano SLX E Mount 2x10spd |
| R. DERAILLEUR | Shimano XT Shadow Plus Direct Mount 10spd |
| F. HUB | Shimano SLX / Centerlock / 32H / 15mm Axle |
| R. HUB | Shimano SLX / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Wheeltech Inferno 23 by SUNringlé |
| TIRES | Maxxis Folding F: Ardent 27.5" x 2.25" R: Ardent Race 27.5" x 2.2" |
| HANDELBAR | Race Face Evolve 1/2 Rise Ø31.8mm x 750mm x 9° Sweep |
| STEM | Race Face 6° x 60-80mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Volt Race |
| SEATPOST | Race Face 30.9mm x 375mm |

*Price, specification and availability subject to change without notice.



THUNDERBOLT 730

CRF506



TECHNOLOGY



IMPROVEMENTS

Shimano M506 Brakes: New I Spec Shifter Mount.

Shimano XT Shadow Plus Rear Derailleur for Chain Management.

GEOMETRY

| FRAME SIZE | | XS | SM | MD | LG | XL |
|------------------------------|---------|-------|-------|-------|-------|-------|
| HEAD ANGLE | degrees | 68.5° | 68.5° | 68.5° | 68.5° | 68.5° |
| SEAT ANGLE | degrees | 74.5° | 74.5° | 74.5° | 74.5° | 74.5° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 381 | 419 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 540 | 565 | 590 | 615 | 645 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 426 | 426 | 426 | 426 | 426 |
| BOTTOM BRACKET DROP | (mm) | 20 | 20 | 20 | 20 | 20 |
| STANDOVER HEIGHT | (mm) | 715 | 715 | 715 | 715 | 715 |
| WHEELBASE | (mm) | 1,072 | 1,098 | 1,124 | 1,150 | 1,181 |
| REACH | (mm) | 381 | 404 | 426 | 449 | 475 |
| STACK | (mm) | 573 | 582 | 591 | 601 | 615 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | FORM™ 7005 Series Custom Hydroformed Alloy, ABC™ Pivots, Tapered Head Tube, Press Fit BB. |
| COLOR | Matte Orange |
| SIZES | XS - S - M - L - XL |
| SHOCK | Fox Float CTD Custom Race Valved, SmoothLink™ Design 120mm, Rebound / Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings |
| FORK | X Fusion Velvet RL2 27.5 Air, 120mm, Lockout / Rebound / 15mm Axle/ |
| HEADSET | Cane Creek Fifteen Series: Z544mm Top / Z556mm Bottom Tapered |
| BRAKE LEVERS | Shimano M506 I-Spec Shifter Mount |
| BRAKES | Shimano M506 Hydraulic Disc 180/160mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | Shimano M552 170-175mm 42/32/24T 3x10spd |
| BOTTOM BRACKET | Shimano SMBB71 Press Fit |
| SHIFTERS | Shimano Deore Rapid Fire I-Spec 3x10spd |
| F. DERAILLEUR | Shimano Deore E-Mount 3x10spd |
| R. DERAILLEUR | Shimano XT Shadow Plus Direct Mount 10spd |
| F. HUB | Shimano 618 / Centerlock / 32H / 15mm Axle |
| R. HUB | Shimano 618 / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Champion |
| RIMS | Wheeltech Inferno 23 by SUNringlé |
| TIRES | Maxxis Folding F: Ardent 27.5" x 2.25" R: Ardent Race 27.5" x 2.2" |
| HANDELBAR | Race Face 3/4 Rise Ø31.8mm x 740mm x 5° Sweep |
| STEM | Race Face 6° x 70-90mm |
| GRIPS | Rocky Mountain XC Kraton |
| SADDLE | WTB Volt |
| SEATPOST | Race Face 30.9mm x 375mm |

*Price, specification and availability subject to change without notice.



THUNDERBOLT 710

CRF503



TECHNOLOGY



IMPROVEMENTS

Manitou Marvel Fork & Radium Expert Shock: Supple TPC Damping and Low Air Pressure system.

Shimano Hydraulic Brakes for Reliable Performance.

High Performance Maxxis Tires.

GEOMETRY

| FRAME SIZE | | XS | SM | MD | LG | XL |
|------------------------------|---------|-------|-------|-------|-------|-------|
| HEAD ANGLE | degrees | 68.5° | 68.5° | 68.5° | 68.5° | 68.5° |
| SEAT ANGLE | degrees | 74.5° | 74.5° | 74.5° | 74.5° | 74.5° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 381 | 419 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 540 | 565 | 590 | 615 | 645 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 426 | 426 | 426 | 426 | 426 |
| BOTTOM BRACKET DROP | (mm) | 20 | 20 | 20 | 20 | 20 |
| STANDOVER HEIGHT | (mm) | 715 | 715 | 715 | 715 | 715 |
| WHEELBASE | (mm) | 1,072 | 1,098 | 1,124 | 1,150 | 1,181 |
| REACH | (mm) | 381 | 404 | 426 | 449 | 475 |
| STACK | (mm) | 573 | 582 | 591 | 601 | 615 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | FORM™ 7005 Series Custom Hydroformed Alloy, ABC™ Pivots, Tapered Head Tube, Press Fit BB. |
| COLOR | Gloss Neon Red |
| SIZES | XS - S - M - L - XL |
| SHOCK | Manitou Radium Expert Custom Valved, SmoothLink™ Design 120mm, Rebound / Lockout |
| FORK | Manitou Marvel LTD.120mm / ACT Air / Compression / Lockout / Rebound / Alloy Steerer |
| HEADSET | Cane Creek Fifteen Series: Z544mm Top / Z556mm Bottom Reducer |
| BRAKE LEVERS | Shimano BL-M395 |
| BRAKES | Shimano BR-M395 Hydraulic Disc 160mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | FSA Gamma Drive 170-175mm 44/32/22T 3x10spd |
| BOTTOM BRACKET | FSA Press Fit Mega Exo |
| SHIFTERS | Sram X5 Triggers 3x10spd |
| F. DERAILLEUR | Sram X7 S3 Direct Mount 3x10spd |
| R. DERAILLEUR | Sram X5 3x10spd |
| F. HUB | Shimano RM35 / Centerlock / 9 x 100mm QR |
| R. HUB | Shimano RM35 / Centerlock / 10 x 135mm QR |
| SPOKES | Stainless |
| RIMS | Wheeltech TD26 by Alex Rims |
| TIRES | Maxxis F: Ardent 27.5" x 2.25" R: Ardent Race 27.5" x 2.2" |
| HANDELBAR | Rocky Mountain Five15 XC Ø31.8mm x 720mm x 5° Sweep |
| STEM | Rocky Mountain L7 7° x 70-90mm |
| GRIPS | Rocky Mountain XC Kraton |
| SADDLE | WTB Volt |
| SEATPOST | Rocky Mountain XC 30.9mm x 350mm |

*Price, specification and availability subject to change without notice.



INSTINCT 999 MSL

CRS555 / CFS555 (frame only)



TECHNOLOGY



IMPROVEMENTS

Stan's Valor Carbon Wheels: 1250g and Increased Stiffness.

Shimano XTR Trail Brakes for Reliable Performance.

High Performance Maxxis Tubeless Tires.

GEOMETRY

| FRAME SIZE | | SM | MD | LG | XL | XXL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 67.7° - 69.3° | 67.7° - 69.3° | 67.7° - 69.3° | 67.7° - 69.3° | 67.7° - 69.3° |
| SEAT ANGLE | degrees | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 394 | 432 | 470 | 508 | 546 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 553 | 577 | 600 | 625 | 650 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 452 | 452 | 452 | 452 | 452 |
| BOTTOM BRACKET DROP | (mm) | 39.6 to 20.7 | 39.6 to 20.7 | 39.6 to 20.7 | 39.6 to 20.7 | 39.6 to 20.7 |
| STANDOVER HEIGHT | (mm) | 736 | 736 | 736 | 736 | 736 |
| WHEELBASE | (mm) | 1110 | 1134 | 1158 | 1183 | 1210 |
| REACH | (mm) | 378 - 395 | 400 - 417 | 420 - 437 | 442 - 459 | 464 - 480 |
| STACK | (mm) | 605 - 594 | 614 - 603 | 624 - 612 | 633 - 621 | 647 - 634 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | SMOOTHWALL™ Carbon. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate |
| COLOR | Matte Carbon |
| SIZES | S - M - L - XL - XXL |
| SHOCK | Fox Float CTD Remote Kashima Custom Trail Valved. SmoothLink™ Design 130mm. Rebound / Remote Climb (X-Firm ProPedal) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate |
| FORK | Fox 32 Float 29 130 FIT CTD Adjust Kashima. 130mm. Rebound / Climb (Lockout) - Trail (3 Position Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer |
| HEADSET | Cane Creek Forty Series: IS42mm Top / IS52mm Bottom Tapered |
| BRAKE LEVERS | Shimano XTR Trail |
| BRAKES | Shimano XTR Ice-Tec Hydraulic Disc 180mm |
| CASSETTE | Sram XG-1199 10-42T 11spd |
| CHAIN | Sram PC-XX1 11spd |
| CRANKS | Race Face Next SL 170-175mm 30T 11spd |
| BOTTOM BRACKET | Race Face Cinch 30mm BB92 Pressfit |
| SHIFTERS | Sram XX1 Trigger 1x11spd |
| F. DERAILLEUR | N/A |
| R. DERAILLEUR | Sram XX1 Type 2 All Mountain 11spd |
| F. HUB | Stan's 3.30Ti Hub / 24H / 15mm Axle |
| R. HUB | Stan's 3.30Ti Hub / 28H / Alloy XD Freehub / 12 x 142mm Axle |
| SPOKES | Sapim Laser |
| RIMS | Stan's Valor Carbon Tubeless Ready |
| TIRES | Maxxis EXO Maxx Speed Tubeless Ready F: Ardent 29" x 2.4" R: Ikon 29" x 2.35" |
| HANDELBAR | Race Face Next Carbon 1/2 Rise Ø35mm x 760mm x 9° Sweep |
| STEM | Race Face Turbine CNC 35mm 6° x 60-80mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Silverado Carbon |
| SEATPOST | RockShox Verber Stealth 30.9mm x 355-420mm |

*Price, specification and availability subject to change without notice.



INSTINCT 990 MSL

CRS554

BC EDITION



TECHNOLOGY



GEOMETRY

| FRAME SIZE | | SM | MD | LG | XL | XXL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 66.7° - 68.3° | 66.7° - 68.3° | 66.7° - 68.3° | 66.7° - 68.3° | 66.7° - 68.3° |
| SEAT ANGLE | degrees | 72.8° - 74.3° | 72.8° - 74.3° | 72.8° - 74.3° | 72.8° - 74.3° | 72.8° - 74.3° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 394 | 432 | 470 | 508 | 546 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 553 | 577 | 600 | 625 | 650 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 452 | 452 | 452 | 452 | 452 |
| BOTTOM BRACKET DROP | (mm) | 31.9 to 12.4 | 31.9 to 12.4 | 31.9 to 12.4 | 31.9 to 12.4 | 31.9 to 12.4 |
| STANDOVER HEIGHT | (mm) | 745 | 745 | 745 | 745 | 745 |
| WHEELBASE | (mm) | 1119 | 1143 | 1167 | 1192 | 1219 |
| REACH | (mm) | 367 - 384 | 389 - 406 | 409 - 426 | 432 - 449 | 453 - 470 |
| STACK | (mm) | 611 - 600 | 621 - 610 | 631 - 620 | 641 - 629 | 655 - 643 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | SMOOTHWALL™ Carbon. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate |
| COLOR | Matte Orange |
| SIZES | S - M - L - XL - XXL |
| SHOCK | RockShox Monarch RT3 Custom BC Valved. SmoothLink™ Design 130mm. Rebound / 3 Position Compression / Adjustable Suspension Rate |
| FORK | RockShox Pike RCT3 29. 140mm. Charger Damper / Rebound / Adjustable 3 Position Compression / 15mm Axle / Tapered Steerer |
| HEADSET | Cane Creek Forty Series: IS42mm Top / IS52mm Bottom Tapered |
| BRAKE LEVERS | Shimano XT |
| BRAKES | Shimano XT Ice-Tec Hydraulic Disc 180mm |
| CASSETTE | Sram XG-1195 10-42T 11spd |
| CHAIN | Sram PC-XX1 11spd |
| CRANKS | Race Face Turbine Cinch 170-175mm 30T Direct Mount 1x11spd |
| BOTTOM BRACKET | Race Face Cinch 30mm BB92 Pressfit |
| SHIFTERS | Sram X01 Trigger 1x11spd |
| F. DERAILLEUR | N/A |
| R. DERAILLEUR | Sram X01 Type 2 All Mountain 11spd |
| F. HUB | Stan's 3.30 Disc / 15mm Axle |
| R. HUB | Stan's 3.30 Disc / 6 Pawl XD Freehub / 142 x 12mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Stan's ZTR Flow EX Tubeless Ready |
| TIRES | Maxxis Minion DHR II Maxx Terra EX0 Tubeless Ready 29" x 2.3" |
| HANDELBAR | Race Face Next 1/2 Rise Ø35mm x 760mm x 9° Sweep |
| STEM | Race Face Turbine 35mm 6° x 50-70mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Silverado SLT Titanium |
| SEATPOST | RockShox Reverb Stealth 30.9mm x 355-420mm |

*Price, specification and availability subject to change without notice.



INSTINCT 970 MSL

CRS552



TECHNOLOGY



IMPROVEMENTS

Race Face Turbine Cinch 30mm Crank: Lighter and Stiffer.

Stan's ZTR Flow Rims: Wider Profile for Stiffer Wheel and Bigger Tire Contact Patch.

High Performance Maxxis Folding Tires.

GEOMETRY

| FRAME SIZE | | SM | MD | LG | XL | XXL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 66.7° - 68.3° | 66.7° - 68.3° | 66.7° - 68.3° | 66.7° - 68.3° | 66.7° - 68.3° |
| SEAT ANGLE | degrees | 72.8° - 74.3° | 72.8° - 74.3° | 72.8° - 74.3° | 72.8° - 74.3° | 72.8° - 74.3° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 394 | 432 | 470 | 508 | 546 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 553 | 577 | 600 | 625 | 650 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 452 | 452 | 452 | 452 | 452 |
| BOTTOM BRACKET DROP | (mm) | 31.9 to 12.4 | 31.9 to 12.4 | 31.9 to 12.4 | 31.9 to 12.4 | 31.9 to 12.4 |
| STANDOVER HEIGHT | (mm) | 745 | 745 | 745 | 745 | 745 |
| WHEELBASE | (mm) | 1119 | 1143 | 1167 | 1192 | 1219 |
| REACH | (mm) | 367 - 384 | 389 - 406 | 409 - 426 | 432 - 449 | 453 - 470 |
| STACK | (mm) | 611 - 600 | 621 - 610 | 631 - 620 | 641 - 629 | 655 - 643 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | SMOOTHWALL™ Carbon. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate |
| COLOR | Matte Carbon |
| SIZES | S - M - L - XL - XXL |
| SHOCK | Fox Float CTD Remote Custom Trail Valved. SmoothLink™ Design 130mm. Rebound / Remote Climb (X-Firm ProPedal) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate |
| FORK | Fox 32 Float 29 130 FIT CTD. 130mm. FIT Damper / Rebound / Climb (Lockout) - Trail (Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer |
| HEADSET | Cane Creek Forty Series: IS42mm Top / IS52mm Bottom Tapered |
| BRAKE LEVERS | Shimano XT I-Spec Shifter Mount |
| BRAKES | Shimano XT Hydraulic Disc 180mm |
| CASSETTE | Shimano HG81 11-36T 10spd |
| CHAIN | Shimano HG95 10spd |
| CRANKS | Race Face Turbine Cinch 170-175mm Bash/36/22T 2x10spd |
| BOTTOM BRACKET | Race Face Cinch 30mm BB92 Pressfit |
| SHIFTERS | Shimano XT Rapid Fire I-Spec 2x10spd |
| F. DERAILLEUR | Sram XO S3 Direct Mount 2x10spd |
| R. DERAILLEUR | Shimano XT Shadow Plus Direct Mount 10spd |
| F. HUB | Shimano XT / Centerlock / 32H / 15mm Axle |
| R. HUB | Shimano XT / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Stan's ZTR Flow Tubeless Ready |
| TIRES | Maxxis F: Ardent EXO Folding 29" x 2.4" R: Ikon EXO Folding 29" x 2.35" |
| HANDELBAR | Race Face Turbine 1/2 Rise Ø35mm x 760mm x 9° Sweep |
| STEM | Race Face Turbine 35mm 6° x 60-80mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Silverado Race |
| SEATPOST | RockShox Reverb Stealth 30.9mm x 355-420mm |

*Price, specification and availability subject to change without notice.



INSTINCT 950 MSL

CRS546



TECHNOLOGY



IMPROVEMENTS

Shimano SLX Brakes for Reliable Performance.

SunRINGLÉ Helix TR27 Rims: Wider Profile and Tubeless Compatible.

X Fusion HiLo Strate Seatpost: Internally Routed Dropper Post.

GEOMETRY

| FRAME SIZE | | SM | MD | LG | XXL | XXL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 67.7° - 69.3° | 67.7° - 69.3° | 67.7° - 69.3° | 67.7° - 69.3° | 67.7° - 69.3° |
| SEAT ANGLE | degrees | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 394 | 432 | 470 | 508 | 546 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 553 | 577 | 600 | 625 | 650 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 452 | 452 | 452 | 452 | 452 |
| BOTTOM BRACKET DROP | (mm) | 39.6 to 20.7 | 39.6 to 20.7 | 39.6 to 20.7 | 39.6 to 20.7 | 39.6 to 20.7 |
| STANDOVER HEIGHT | (mm) | 736 | 736 | 736 | 736 | 736 |
| WHEELBASE | (mm) | 1110 | 1134 | 1158 | 1183 | 1210 |
| REACH | (mm) | 378 - 395 | 400 - 417 | 420 - 437 | 442 - 459 | 464 - 480 |
| STACK | (mm) | 605 - 594 | 614 - 603 | 624 - 612 | 633 - 621 | 647 - 634 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | SMOOTHWALL™ Carbon. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate |
| COLOR | Matte Dark Red |
| SIZES | S - M - L - XL - XXL |
| SHOCK | Fox Float CTD Custom Race Valved. SmoothLink™ Design 130mm. Rebound / Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate |
| FORK | Fox 32 Float 29 130 CTD. 130mm. Rebound / Climb (Lockout) - Trail (Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer |
| HEADSET | Cane Creek Fiften Series: IS42mm Top / IS52mm Bottom Tapered |
| BRAKE LEVERS | Shimano SLX |
| BRAKES | Shimano SLX Hydraulic Disc 180mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | Race Face Evolve 170-175mm Bash/36/22T 2x10spd |
| BOTTOM BRACKET | Race Face Press Fit Team XC |
| SHIFTERS | Sram X7 Triggers 2x10spd |
| F. DERAILLEUR | Sram X7 S3 Direct Mount 2x10spd |
| R. DERAILLEUR | Sram X9 Type 2 All Mountain 10spd |
| F. HUB | Shimano SLX / Centerlock / 32H / 15mm Axle |
| R. HUB | Shimano SLX / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Wheeltech Helix TR27 Tubeless Compatible by SUNringlé |
| TIRES | Maxxis F: Ardent EX0 Folding 29" x 2.4" R: Ikon EX0 Folding 29" x 2.35" |
| HANDELBAR | Race Face Evolve 1/2 Rise Ø31.8mm x 750mm x 9° Sweep |
| STEM | Race Face 6° x 60-80mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Volt Race |
| SEATPOST | X Fusion HiLo Strate 30.9mm x 420mm |

*Price, specification and availability subject to change without notice.



INSTINCT 950

CRS544

BC EDITION



TECHNOLOGY



GEOMETRY

| FRAME SIZE | | SM | MD | LG | XL | XXL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 66.7° - 68.3° | 66.7° - 68.3° | 66.7° - 68.3° | 66.7° - 68.3° | 66.7° - 68.3° |
| SEAT ANGLE | degrees | 72.8° - 74.3° | 72.8° - 74.3° | 72.8° - 74.3° | 72.8° - 74.3° | 72.8° - 74.3° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 394 | 432 | 470 | 508 | 546 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 553 | 577 | 600 | 625 | 650 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 452 | 452 | 452 | 452 | 452 |
| BOTTOM BRACKET DROP | (mm) | 31.9 to 12.4 | 31.9 to 12.4 | 31.9 to 12.4 | 31.9 to 12.4 | 31.9 to 12.4 |
| STANDOVER HEIGHT | (mm) | 745 | 745 | 745 | 745 | 745 |
| WHEELBASE | (mm) | 1119 | 1143 | 1167 | 1192 | 1219 |
| REACH | (mm) | 367 - 384 | 389 - 406 | 409 - 426 | 432 - 449 | 453 - 470 |
| STACK | (mm) | 611 - 600 | 621 - 610 | 631 - 620 | 641 - 629 | 655 - 643 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | FORM™ 7005 Series Custom Hydroformed Alloy. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate |
| COLOR | Matte Blue |
| SIZES | S - M - L - XL - XXL |
| SHOCK | X Fusion 02 RLX Custom Trail Valved. SmoothLink™ Design 130mm. Rebound / 3 Position Compression Settings / Adjustable Suspension Rate |
| FORK | X Fusion 140 Trace RL2. 34mm Stanchions / Lockout / Rebound / 15mm XLock / Tapered Steerer |
| HEADSET | Cane Creek Fifteen Series: Z544mm Top / Z556mm Bottom Tapered |
| BRAKE LEVERS | Shimano SLX |
| BRAKES | Shimano SLX Ice-Tec Hydraulic Disc 180mm |
| CASSETTE | Sram XG-1180 10-42T 11spd |
| CHAIN | KMC X11 11spd |
| CRANKS | Race Face Ride 170-175mm 30T 1x11spd |
| BOTTOM BRACKET | Race Face Press Fit Team XC |
| SHIFTERS | Sram X1 Trigger 1x11spd |
| F. DERAILLEUR | N/A |
| R. DERAILLEUR | Sram X1 Type 2 All Mountain 11spd |
| F. HUB | Sram MTH 716 / 6 Bolt / 15mm Axle |
| R. HUB | Sram MTH 746 / 6 Bolt / XD Freehub Body / 12 x 142mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Wheeltech Inferno 27 by SUNringlé |
| TIRES | Maxxis DHR II EXO Folding 29" x 2.3" |
| HANDELBAR | Race Face Evolve 1/2 Rise Ø31.8mm x 750mm x 9° Sweep |
| STEM | Race Face 6° x 60-80mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Volt Race |
| SEATPOST | X Fusion HiLo Ace 30.9mm x 420mm |

*Price, specification and availability subject to change without notice.



INSTINCT 950

CRS543



TECHNOLOGY



IMPROVEMENTS

SunRINGLÉ Inferno 27 Rims: Wider Profile for Stiffer Wheel and Bigger Tire Contact Patch.

High Performance Maxxis Folding Tires.

GEOMETRY

| FRAME SIZE | | SM | MD | LG | XL | XXL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 67.7° - 69.3° | 67.7° - 69.3° | 67.7° - 69.3° | 67.7° - 69.3° | 67.7° - 69.3° |
| SEAT ANGLE | degrees | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 394 | 432 | 470 | 508 | 546 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 553 | 577 | 600 | 625 | 650 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 452 | 452 | 452 | 452 | 452 |
| BOTTOM BRACKET DROP | (mm) | 39.6 to 20.7 | 39.6 to 20.7 | 39.6 to 20.7 | 39.6 to 20.7 | 39.6 to 20.7 |
| STANDOVER HEIGHT | (mm) | 736 | 736 | 736 | 736 | 736 |
| WHEELBASE | (mm) | 1110 | 1134 | 1158 | 1183 | 1210 |
| REACH | (mm) | 378 - 395 | 400 - 417 | 420 - 437 | 442 - 459 | 464 - 480 |
| STACK | (mm) | 605 - 594 | 614 - 603 | 624 - 612 | 633 - 621 | 647 - 634 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | FORM™ 7005 Series Custom Hydroformed Alloy. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate |
| COLOR | Matte Black |
| SIZES | S - M - L - XL - XXL |
| SHOCK | Fox Float CTD Custom Race Valved. SmoothLink™ Design 130mm. Rebound / Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate |
| FORK | Fox 32 Float 29 130 CTD. 130mm. Rebound / Climb (Lockout) - Trail (Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer |
| HEADSET | Cane Creek Fifteen Series: Z544mm Top / Z556mm Bottom Tapered |
| BRAKE LEVERS | Shimano SLX I-Spec Shifter Mount |
| BRAKES | Shimano SLX Hydraulic Disc 180mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | Race Face Evolve 170-175mm Bash/36/22T 2x10spd |
| BOTTOM BRACKET | Race Face Press Fit Team XC |
| SHIFTERS | Shimano SLX Rapid Fire I-Spec 2x10spd |
| F. DERAILLEUR | Sram X7 S3 Direct Mount 2x10spd |
| R. DERAILLEUR | Shimano XT Shadow Plus Direct Mount 10spd |
| F. HUB | Shimano SLX / Centerlock / 32H / 15mm Axle |
| R. HUB | Shimano SLX / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Wheeltech Inferno 27 by SUNringlé |
| TIRES | Maxxis F: Ardent EXO Folding 29" x 2.4" R: Ikon EXO Folding 29" x 2.35" |
| HANDELBAR | Race Face Evolve 1/2 Rise Ø31.8mm x 750mm x 9° Sweep |
| STEM | Race Face 6° x 60-80mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Volt Race |
| SEATPOST | Rocky Mountain SL 30.9mm x 400mm |

*Price, specification and availability subject to change without notice.



INSTINCT 930

CRS540



TECHNOLOGY



IMPROVEMENTS

Manitou Minute Expert Fork: Supple TPC Damping and Hydraulic Bottom Out Control.

SunRINGLÉ Inferno 27 Rims: Wider Profile for Stiffer Wheel and Bigger Tire Contact Patch.

High Performance Maxxis Folding Tires.

GEOMETRY

| FRAME SIZE | | SM | MD | LG | XL | XXL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 67.7° - 69.3° | 67.7° - 69.3° | 67.7° - 69.3° | 67.7° - 69.3° | 67.7° - 69.3° |
| SEAT ANGLE | degrees | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° | 73.7° - 75.3° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 394 | 432 | 470 | 508 | 546 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 553 | 577 | 600 | 625 | 650 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 452 | 452 | 452 | 452 | 452 |
| BOTTOM BRACKET DROP | (mm) | 39.6 to 20.7 | 39.6 to 20.7 | 39.6 to 20.7 | 39.6 to 20.7 | 39.6 to 20.7 |
| STANDOVER HEIGHT | (mm) | 736 | 736 | 736 | 736 | 736 |
| WHEELBASE | (mm) | 1110 | 1134 | 1158 | 1183 | 1210 |
| REACH | (mm) | 378 - 395 | 400 - 417 | 420 - 437 | 442 - 459 | 464 - 480 |
| STACK | (mm) | 605 - 594 | 614 - 603 | 624 - 612 | 633 - 621 | 647 - 634 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | FORM™ 7005 Series Custom Hydroformed Alloy. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate |
| COLOR | Matte Blue |
| SIZES | S - M - L - XL - XXL |
| SHOCK | Fox Float CTD Custom Race Valved. SmoothLink™ Design 130mm. Rebound / Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate |
| FORK | Manitou Minute Expert. 130mm. TPC Absolute+ Damper / Hydraulic Bottom Out / Compression / Lockout / Rebound / 15mm Hexlock Axle / Tapered Steerer |
| HEADSET | Cane Creek Fifteen Series: Z544mm Top / Z556mm Bottom Tapered |
| BRAKE LEVERS | Shimano M506 I-Spec Shifter Mount |
| BRAKES | Shimano M506 Hydraulic Disc 180mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | Race Face Ride 170-175mm Bash/36/22T 2x10spd |
| BOTTOM BRACKET | Race Face Press Fit Team XC |
| SHIFTERS | Shimano Deore Rapid Fire I-Spec 2x10spd |
| F. DERAILLEUR | Sram X5 S3 Direct Mount 2x10spd |
| R. DERAILLEUR | Shimano XT Shadow Plus Direct Mount 10spd |
| F. HUB | Shimano 618 / Centerlock / 32H / 15mm Axle |
| R. HUB | Shimano 618 / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Champion |
| RIMS | Wheeltech Inferno 27 by SunRinglé |
| TIRES | Maxxis F: Ardent EXO Folding 29" x 2.4" R: Ikon EXO Folding 29" x 2.35" |
| HANDELBAR | Race Face Ride 1/2 Rise Ø31.8mm x 740mm x 9° Sweep |
| STEM | Race Face 6° x 60-80mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Volt Race |
| SEATPOST | Rocky Mountain SL 30.9mm x 400mm |

*Price, specification and availability subject to change without notice.



ALTITUDE 799 MSL

CRE521 / CFE521 (frame only)



TECHNOLOGY



IMPROVEMENTS

Shimano XTR Trail Brakes for Reliable Performance.

Reynolds All Mountain Carbon Wheels: Reliable DT Swiss 240s Hubs and Stiff, Tubeless Reynolds Carbon Rims.

High Performance Maxxis Tubeless Tires.

GEOMETRY

| FRAME SIZE | | XS | SM | MD | LG | XL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 66.6° - 68.3° | 66.6° - 68.3° | 66.6° - 68.3° | 66.6° - 68.3° | 66.6° - 68.3° |
| SEAT ANGLE | degrees | 73.6° - 75.3° | 73.6° - 75.3° | 73.6° - 75.3° | 73.6° - 75.3° | 73.6° - 75.3° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 381 | 419 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 540 | 565 | 585 | 605 | 630 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 428 | 428 | 428 | 428 | 428 |
| BOTTOM BRACKET DROP | (mm) | -9.8 to +10.3 | -9.8 to +10.3 | -9.8 to +10.3 | -9.8 to +10.3 | -9.8 to +10.3 |
| STANDOVER HEIGHT | (mm) | 734 | 734 | 734 | 734 | 734 |
| WHEELBASE | (mm) | 1095 | 1120 | 1142 | 1163 | 1189 |
| REACH | (mm) | 370 - 387 | 392 - 410 | 410 - 427 | 427 - 444 | 448 - 465 |
| STACK | (mm) | 577 - 586 | 587 - 595 | 596 - 604 | 605 - 614 | 619 - 627 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | SMOOTHWALL™ Carbon. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate |
| COLOR | Matte Carbon |
| SIZES | XS - S - M - L - XL |
| SHOCK | Fox Float CTD Remote Kashima Custom Trail Valved. SmoothLink™ Design 150mm. Rebound / Remote Climb (X-Firm ProPedal) - Trail (ProPedal) - Descend (Open) Settings / Kashima Coating / Adjustable Suspension Rate |
| FORK | Fox 34 Float 150 Kashima FIT CTD 27.5. 150mm. FIT Damper / Rebound / Climb (Lockout) - Trail (3 Position Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer / Kashima Coating |
| HEADSET | Cane Creek Forty Series: 1542mm Top / 52mm Bottom Tapered |
| BRAKE LEVERS | Shimano XTR Trail |
| BRAKES | Shimano XTR Ice-Tec Hydraulic Disc 180mm |
| CASSETTE | Sram XG-1199 10-42T 11spd |
| CHAIN | Sram PC-XX1 11spd |
| CRANKS | Race Face Next SL 170-175mm Direct Mount 32T 11spd |
| BOTTOM BRACKET | Race Face Cinch 30mm BB92 Pressfit |
| SHIFTERS | Sram XX1 Trigger 1x11spd |
| F. DERAILLEUR | N/A |
| R. DERAILLEUR | Sram XX1 Type 2 All Mountain 11spd |
| F. HUB | DT Swiss 240 / Centerlock / 28H / 15mm Axle |
| R. HUB | DT Swiss 240 / Centerlock / 28H / Alloy XD Freehub / 12 x 142mm Axle |
| SPOKES | DT Swiss Aerolite |
| RIMS | Reynolds All Mtn Tubeless Ready Carbon |
| TIRES | Maxxis F: Minion DHF EXO Maxx Terra 27.5" x 2.3" R: Ardent EXO Dual 27.5" x 2.4" Tubeless Ready Folding |
| HANDELBAR | Race Face Next Carbon 1/2 Rise Ø35mm x 760mm x 9° Sweep |
| STEM | Race Face Turbine CNC 35mm 6° x 60-70mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Silverado Carbon |
| SEATPOST | RockShox Reverb Stealth 30.9mm x 355-420mm |

*Price, specification and availability subject to change without notice.



ALTITUDE 790 MSL

CRE519/CFE519 (frame only)



TECHNOLOGY



SPECIFICATIONS

GEOMETRY

| FRAME SIZE | | XS | SM | MD | LG | XL |
|------------------------------|---------|----------------|----------------|----------------|----------------|----------------|
| HEAD ANGLE | degrees | 66.2° - 67.8° | 66.2° - 67.8° | 66.2° - 67.8° | 66.2° - 67.8° | 66.2° - 67.8° |
| SEAT ANGLE | degrees | 73.2° - 74.8° | 73.2° - 74.8° | 73.2° - 74.8° | 73.2° - 74.8° | 73.2° - 74.8° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 381 | 419 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 540 | 565 | 585 | 605 | 630 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 428 | 428 | 428 | 428 | 428 |
| BOTTOM BRACKET DROP | (mm) | -13.6 to +7.27 | -13.6 to +7.27 | -13.6 to +7.27 | -13.6 to +7.27 | -13.6 to +7.27 |
| STANDOVER HEIGHT | (mm) | 736 | 736 | 736 | 736 | 736 |
| WHEELBASE | (mm) | 1099 | 1125 | 1146 | 1168 | 1195 |
| REACH | (mm) | 365 | 387 | 405 | 422 | 443 |
| STACK | (mm) | 584 | 593 | 603 | 612 | 626 |
| | | 593 | 602 | 611 | 621 | 634 |

* More details on measurements on demand.

| | |
|----------------|---|
| FRAME | SMOOTHWALL™ Carbon. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate |
| COLOR | Matte Green |
| SIZES | XS - S - M - L - XL |
| SHOCK | Fox Float X Remote Kashima CTD Custom Trail Valved. SmoothLink™ Design 150mm. Rebound / Remote Climb (X-Firm ProPedal) - Trail (ProPedal) - Descend (Open) Settings / Bottom Out Control / Kashima Coating / Adjustable Suspension Rate |
| FORK | Fox 36 Float 160 Kashima RC2 27.5. 160mm. RC2 Damper / Rebound / Hi-Lo Speed Compression / 20mm Axle / Tapered Steerer / Kashima Coating |
| HEADSET | Cane Creek Forty Series: 1542mm Top / 52mm Bottom Tapered |
| BRAKE LEVERS | Shimano XT |
| BRAKES | Shimano XT Ice-Tec Hydraulic Disc 180mm |
| CASSETTE | Sram XG-1195 10-42T 11spd |
| CHAIN | Sram PC-XX1 11spd |
| CRANKS | Race Face Turbine Cinch 170-175mm 34T Direct Mount 1x11spd |
| BOTTOM BRACKET | Race Face Cinch 30mm BB92 Pressfit |
| SHIFTERS | Sram X01 Trigger 1x11spd |
| F. DERAILLEUR | N/A |
| R. DERAILLEUR | Sram X01 Type 2 All Mountain 11spd |
| F. HUB | Stan's 3.30 HD Disc / 20mm Axle |
| R. HUB | Stan's 3.30 HD Disc / 6 Pawl Freehub / 142 x 12mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Stan's ZTR Flow EX Tubeless Ready |
| TIRES | Maxxis Minion DHR II EXO Maxx Terra Tubeless Ready Folding 27.5" x 2.3" |
| HANDELBAR | Race Face SixC 3/4 Rise Ø35mm x 800mm x 9° Sweep |
| STEM | Race Face Turbine CNC 35mm x 6° x 50-60mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Silverado SLT Titanium |
| SEATPOST | RockShox Reverb Stealth 30.9mm x 355-420mm |

*Price, specification and availability subject to change without notice.



ALTITUDE 770 MSL

CRE515



TECHNOLOGY



IMPROVEMENTS

Race Face Turbine Cinch 30mm Crank: Lighter and Stiffer.

Stan's ZTR Flow Rims: Wider Profile for Stiffer Wheel and Bigger Tire Contact Patch.

High Performance Maxxis Folding Tires.

GEOMETRY

| FRAME SIZE | | XS | SM | MD | LG | XL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 66.6° - 68.3° | 66.6° - 68.3° | 66.6° - 68.3° | 66.6° - 68.3° | 66.6° - 68.3° |
| SEAT ANGLE | degrees | 73.6° - 75.3° | 73.6° - 75.3° | 73.6° - 75.3° | 73.6° - 75.3° | 73.6° - 75.3° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 381 | 419 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 540 | 565 | 585 | 605 | 630 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 428 | 428 | 428 | 428 | 428 |
| BOTTOM BRACKET DROP | (mm) | -9.8 to +10.3 | -9.8 to +10.3 | -9.8 to +10.3 | -9.8 to +10.3 | -9.8 to +10.3 |
| STANDOVER HEIGHT | (mm) | 734 | 734 | 734 | 734 | 734 |
| WHEELBASE | (mm) | 1095 | 1120 | 1142 | 1163 | 1189 |
| REACH | (mm) | 370 - 387 | 392 - 410 | 410 - 427 | 427 - 444 | 448 - 465 |
| STACK | (mm) | 577 - 586 | 587 - 595 | 596 - 604 | 605 - 614 | 619 - 627 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | SMOOTHWALL™ Carbon. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate |
| COLOR | Matte Carbon |
| SIZES | XS - S - M - L - XL |
| SHOCK | Fox Float Remote CTD Custom Trail Valved. SmoothLink™ Design 150mm. Rebound / Remote Climb (X-Firm ProPedal) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate |
| FORK | Fox 34 Float 150 FIT CTD 27.5. 150mm. FIT Damper / Rebound / Climb (Lockout) - Trail (Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer |
| HEADSET | Cane Creek Forty Series: 1542mm Top / 52mm Bottom Tapered |
| BRAKE LEVERS | Shimano XT I-Spec Shifter Mount |
| BRAKES | Shimano XT Hydraulic Disc 180mm |
| CASSETTE | Shimano HG81 11-36T 10spd |
| CHAIN | Shimano HG95 10spd |
| CRANKS | Race Face Turbine Cinch 170-175mm Bash/36/22T 2x10spd |
| BOTTOM BRACKET | Race Face Cinch 30mm BB92 Pressfit |
| SHIFTERS | Shimano XT Rapid Fire I-Spec 2x10spd |
| F. DERAILLEUR | Sram XO S3 Direct Mount 2x10spd |
| R. DERAILLEUR | Shimano XT Shadow Plus Direct Mount 10spd |
| F. HUB | Shimano XT / Centerlock / 32H / 15mm Axle |
| R. HUB | Shimano XT / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Stan's ZTR Flow Tubeless Ready |
| TIRES | Maxxis F: Minion DHF EX0 Folding 27.5" x 2.30" R: Ardent EX0 Folding 27.5" x 2.4" |
| HANDELBAR | Race Face Turbine 1/2 Rise 035mm x 760mm x 9° Sweep |
| STEM | Race Face Turbine 35mm 6° x 60-70mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Silverado Race |
| SEATPOST | RockShox Verberb Stealth 30.9mm x 355-420mm |

*Price, specification and availability subject to change without notice.



ALTITUDE 750 MSL

CRE512



TECHNOLOGY



IMPROVEMENTS

Shimano SLX Brakes for Reliable Performance.

SunRINGLÉ Helix TR27 Rims: Wider Profile and Tubeless Compatible.

High Performance Maxxis Folding Tires.

GEOMETRY

| FRAME SIZE | | XS | SM | MD | LG | XL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 66.6° - 68.3° | 66.6° - 68.3° | 66.6° - 68.3° | 66.6° - 68.3° | 66.6° - 68.3° |
| SEAT ANGLE | degrees | 73.6° - 75.3° | 73.6° - 75.3° | 73.6° - 75.3° | 73.6° - 75.3° | 73.6° - 75.3° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 381 | 419 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 540 | 565 | 585 | 605 | 630 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 428 | 428 | 428 | 428 | 428 |
| BOTTOM BRACKET DROP | (mm) | -9.8 to +10.3 | -9.8 to +10.3 | -9.8 to +10.3 | -9.8 to +10.3 | -9.8 to +10.3 |
| STANDOVER HEIGHT | (mm) | 734 | 734 | 734 | 734 | 734 |
| WHEELBASE | (mm) | 1095 | 1120 | 1142 | 1163 | 1189 |
| REACH | (mm) | 370 - 387 | 392 - 410 | 410 - 427 | 427 - 444 | 448 - 465 |
| STACK | (mm) | 577 - 586 | 587 - 595 | 596 - 604 | 605 - 614 | 619 - 627 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | SMOOTHWALL™ Carbon Front Triangle. FORM™ 7005 Series Custom Hydroformed Rear Triangle. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate |
| COLOR | Matte Blue |
| SIZES | XS - S - M - L - XL |
| SHOCK | Fox Float Remote CTD Custom Race Valved. SmoothLink™ Design 150mm. Rebound / Remote Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate |
| FORK | Fox 34 Float 150 CTD 27.5. 150mm. Rebound / Climb (Lockout) - Trail (Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer |
| HEADSET | Cane Creek Fifteen Series: IS42mm Top / 52mm Bottom Tapered |
| BRAKE LEVERS | Shimano SLX |
| BRAKES | Shimano SLX Hydraulic Disc 180mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | Race Face Turbine 170-175mm Bash/36/22T 2x10spd |
| BOTTOM BRACKET | Race Face Press Fit Team XC |
| SHIFTERS | Sram X7 Triggers 2x10spd |
| F. DERAILLEUR | Sram X7 S3 Direct Mount 2x10spd |
| R. DERAILLEUR | Sram X9 Type 2 All Mountain 10spd |
| F. HUB | Shimano SLX / Centerlock / 32H / 15mm Axle |
| R. HUB | Shimano SLX / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Wheeltech Helix TR27 Tubeless Compatible by SUNringlé |
| TIRES | Maxxis F: Minion DHF EX0 Folding 27.5" x 2.3" R: Ardent EX0 Folding 27.5" x 2.4" |
| HANDELBAR | Race Face Evolve 1/2 Rise Ø31.8mm x 750mm x 9° Sweep |
| STEM | Race Face 6° x 60-70mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Volt Race |
| SEATPOST | X Fusion HiLo Strate 30.9mm x 420mm |

*Price, specification and availability subject to change without notice.



ALTITUDE 750 MSL

CRE505



TECHNOLOGY



GEOMETRY

| FRAME SIZE | | XS | SM | MD | LG | XL |
|------------------------------|---------|----------------|----------------|----------------|----------------|----------------|
| HEAD ANGLE | degrees | 66.2° - 67.8° | 66.2° - 67.8° | 66.2° - 67.8° | 66.2° - 67.8° | 66.2° - 67.8° |
| SEAT ANGLE | degrees | 73.2° - 74.8° | 73.2° - 74.8° | 73.2° - 74.8° | 73.2° - 74.8° | 73.2° - 74.8° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 381 | 419 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 540 | 565 | 585 | 605 | 630 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 428 | 428 | 428 | 428 | 428 |
| BOTTOM BRACKET DROP | (mm) | -13.6 to +7.27 | -13.6 to +7.27 | -13.6 to +7.27 | -13.6 to +7.27 | -13.6 to +7.27 |
| STANDOVER HEIGHT | (mm) | 736 | 736 | 736 | 736 | 736 |
| WHEELBASE | (mm) | 1099 | 1125 | 1146 | 1168 | 1195 |
| REACH | (mm) | 365 | 387 | 405 | 422 | 443 |
| STACK | (mm) | 584 | 593 | 603 | 612 | 626 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | SMOOTHWALL™ Carbon Front Triangle. FORM™ 7005 Series Custom Hydroformed Rear Triangle. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate |
| COLOR | Matte Orange |
| SIZES | XS - S - M - L - XL |
| SHOCK | X Fusion 02 RL Remote Custom Race Valved. SMOOTHLINK™ Design 150mm. Rebound / Remote Trail Threshold Lockout / Adjustable Suspension Rate |
| FORK | X Fusion Sweep RL2. 160mm. 34mm Stanchions / Lockout / Rebound / 15mm XLock / Tapered Steerer |
| HEADSET | Cane Creek Fifteen Series: IS42mm Top / 52mm Bottom Tapered |
| BRAKE LEVERS | Shimano SLX |
| BRAKES | Shimano SLX Ice-Tec Hydraulic Disc 180mm |
| CASSETTE | Sram XG-1180 10-42T 11spd |
| CHAIN | KMC X11 11spd |
| CRANKS | Race Face Ride 170-175mm 32T 1x11spd |
| BOTTOM BRACKET | Race Face Press Fit Team XC |
| SHIFTERS | Sram X1 Trigger 1x11spd |
| F. DERAILLEUR | N/A |
| R. DERAILLEUR | Sram X1 Type 2 All Mountain 11spd |
| F. HUB | Sram MTH 716 / 6 Bolt / 15mm Axle |
| R. HUB | Sram MTH 746 / 6 Bolt / XD Freehub Body / 12 x 142mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Wheeltech Inferno 27 by SUNringlé |
| TIRES | Maxxis Minion DHR II EX0 Folding 27.5" x 2.3" |
| HANDELBAR | Race Face Evolve 1/2 Rise Ø31.8mm x 750mm x 9° Sweep |
| STEM | Race Face Respond 6° x 45-60mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Volt Race |
| SEATPOST | X Fusion HiLo Ace 30.9mm x 420mm |

*Price, specification and availability subject to change without notice.



ALTITUDE 750

CRE506



TECHNOLOGY



IMPROVEMENTS

SunRINGLÉ Inferno 27 Rims: Wider Profile for Stiffer Wheel and Bigger Tire Contact Patch.

High Performance Maxxis Folding Tires.

GEOMETRY

| FRAME SIZE | | XS | SM | MD | LG | XL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 66.6° - 68.3° | 66.6° - 68.3° | 66.6° - 68.3° | 66.6° - 68.3° | 66.6° - 68.3° |
| SEAT ANGLE | degrees | 73.6° - 75.3° | 73.6° - 75.3° | 73.6° - 75.3° | 73.6° - 75.3° | 73.6° - 75.3° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 381 | 419 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 540 | 565 | 585 | 605 | 630 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 428 | 428 | 428 | 428 | 428 |
| BOTTOM BRACKET DROP | (mm) | -9.8 to +10.3 | -9.8 to +10.3 | -9.8 to +10.3 | -9.8 to +10.3 | -9.8 to +10.3 |
| STANDOVER HEIGHT | (mm) | 734 | 734 | 734 | 734 | 734 |
| WHEELBASE | (mm) | 1095 | 1120 | 1142 | 1163 | 1189 |
| REACH | (mm) | 370 - 387 | 392 - 410 | 410 - 427 | 427 - 444 | 448 - 465 |
| STACK | (mm) | 577 - 586 | 587 - 595 | 596 - 604 | 605 - 614 | 619 - 627 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | FORM™ 7005 Series Custom Hydroformed Alloy. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate |
| COLOR | Matte Black |
| SIZES | XS - S - M - L - XL |
| SHOCK | Fox Float CTD Custom Race Valved. SmoothLink™ Design 150mm. Rebound / Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate |
| FORK | Fox 34 Float 150 CTD 27.5. 150mm. Rebound / Climb (Lockout) - Trail (Compression) - Descend (Open) Settings / 15mm Axle / Tapered Steerer |
| HEADSET | Cane Creek Fifteen Series: Z544mm Top / Z556mm Bottom Tapered |
| BRAKE LEVERS | Shimano SLX I-Spec Shifter Mount |
| BRAKES | Shimano SLX Hydraulic Disc 180mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | Race Face Evolve 170-175mm Bash/36/22T 2x10spd |
| BOTTOM BRACKET | Race Face Press Fit Team XC |
| SHIFTERS | Shimano SLX Rapid Fire I-Spec 2x10spd |
| F. DERAILLEUR | Sram X7 S3 Direct Mount 2x10spd |
| R. DERAILLEUR | Shimano XT Shadow Plus Direct Mount 10spd |
| F. HUB | Shimano SLX / Centerlock / 32H / 15mm Axle |
| R. HUB | Shimano SLX / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Wheeltech Inferno 27 by SUNRINGLÉ |
| TIRES | Maxxis F: Minion DHF EX0 Folding 27.5" x 2.3" R: Ardent EX0 Folding 27.5" x 2.4" |
| HANDELBAR | Race Face Evolve 1/2 Rise Ø31.8mm x 750mm x 9° Sweep |
| STEM | Race Face 6° x 60-70mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Volt Race |
| SEATPOST | Race Face 30.9mm x 375mm |

*Price, specification and availability subject to change without notice.



ALTITUDE 730

CRE503



TECHNOLOGY



IMPROVEMENTS

Shimano Deore Brakes for Reliable Performance.

SunRINGLÉ Inferno 27 Rims: Wider Profile for Stiffer Wheel and Bigger Tire Contact Patch.

High Performance Maxxis Folding Tires.

GEOMETRY

| FRAME SIZE | | XS | SM | MD | LG | XL |
|------------------------------|---------|---------------|---------------|---------------|---------------|---------------|
| HEAD ANGLE | degrees | 66.6° - 68.3° | 66.6° - 68.3° | 66.6° - 68.3° | 66.6° - 68.3° | 66.6° - 68.3° |
| SEAT ANGLE | degrees | 73.6° - 75.3° | 73.6° - 75.3° | 73.6° - 75.3° | 73.6° - 75.3° | 73.6° - 75.3° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 381 | 419 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 540 | 565 | 585 | 605 | 630 |
| HEAD TUBE LENGTH | (mm) | 100 | 110 | 120 | 130 | 145 |
| CHAINSTAY LENGTH | (mm) | 428 | 428 | 428 | 428 | 428 |
| BOTTOM BRACKET DROP | (mm) | -9.8 to +10.3 | -9.8 to +10.3 | -9.8 to +10.3 | -9.8 to +10.3 | -9.8 to +10.3 |
| STANDOVER HEIGHT | (mm) | 734 | 734 | 734 | 734 | 734 |
| WHEELBASE | (mm) | 1095 | 1120 | 1142 | 1163 | 1189 |
| REACH | (mm) | 370 - 387 | 392 - 410 | 410 - 427 | 427 - 444 | 448 - 465 |
| STACK | (mm) | 577 - 586 | 587 - 595 | 596 - 604 | 605 - 614 | 619 - 627 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | FORM™ 7005 Series Custom Hydroformed Alloy. ABC™ Pivots. Tapered Head Tube. Press Fit BB. Internal Cable Routing. ISCG05 Tabs. RIDE-9™ Adjustable Geometry + Suspension Rate |
| COLOR | Matte Black |
| SIZES | XS - S - M - L - XL |
| SHOCK | Fox Float CTD Custom Race Valved. SmoothLink™ Design 150mm. Rebound / Climb (Lockout) - Trail (ProPedal) - Descend (Open) Settings / Adjustable Suspension Rate |
| FORK | X Fusion Sweep RL2 Air 27.5. 150mm. 34mm Stanchions / Lockout / Rebound / 15mm XLock / Tapered Steerer |
| HEADSET | Cane Creek Fifteen Series: Z544mm Top / Z556mm Bottom Tapered |
| BRAKE LEVERS | Shimano Deore |
| BRAKES | Shimano Deore Hydraulic Disc 180mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | Race Face Ride 170-175mm Bash/36/22T 2x10spd |
| BOTTOM BRACKET | Race Face Press Fit Team XC |
| SHIFTERS | Sram X5 Triggers 2x10spd |
| F. DERAILLEUR | Sram X5 S3 Direct Mount 2x10spd |
| R. DERAILLEUR | Sram X9 Type 2 All Mountain 10spd |
| F. HUB | Shimano 618 / Centerlock / 32H / 15mm Axle |
| R. HUB | Shimano 618 / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Champion |
| RIMS | Wheeltech Inferno 27 by SUNringlé |
| TIRES | Maxxis F: Minion DHF EX0 Folding 27.5" x 2.3" R: Ardent EX0 Folding 27.5" x 2.4" |
| HANDELBAR | Race Face Ride 1/2 Rise Ø31.8mm x 740mm x 9° Sweep |
| STEM | Race Face 6° x 60-70mm |
| GRIPS | Rocky Mountain XC Kraton |
| SADDLE | WTB Volt |
| SEATPOST | Race Face 30.9mm x 375mm |

*Price, specification and availability subject to change without notice.



VERTEX 990 RSL

CRR521 / CFR521 (frame only)



TECHNOLOGY



IMPROVEMENTS

Sram X01 11spd Drivetrain for Light Weight And Simplicity.

Shimano XT Brakes for Reliable Performance.

High Performance Maxxis Folding Tubeless Tires.

GEOMETRY

| FRAME SIZE | | SM | MD | LG | XL |
|------------------------------|---------|--------|--------|--------|--------|
| HEAD ANGLE | degrees | 70.25° | 70.25° | 70.25° | 70.25° |
| SEAT ANGLE | degrees | 73° | 73° | 73° | 73° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 394 | 432 | 470 | 508 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 570 | 592 | 615 | 638 |
| HEAD TUBE LENGTH | (mm) | 95 | 100 | 115 | 130 |
| CHAINSTAY LENGTH | (mm) | 433 | 433 | 433 | 433 |
| BOTTOM BRACKET DROP | (mm) | 56 | 56 | 56 | 56 |
| STANDOVER HEIGHT | (mm) | 738 | 752 | 776 | 808 |
| WHEELBASE | (mm) | 1065 | 1087 | 1111 | 1134 |
| REACH | (mm) | 384 | 405 | 424 | 442 |
| STACK | (mm) | 607 | 612 | 626 | 640 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | C13 Hi Mod Carbon Smoothwall Monocoque. Tapered Head Tube. Press Fit BB. Internal Cable Routing. |
| COLOR | Matte Carbon |
| SIZES | S - M - L - XL |
| FORK | RockShox SID RL Remote 29-100mm. Motion Control DNA / Rebound / Remote Lockout / 15mm Maxle Lite / Tapered Steerer |
| HEADSET | Cane Creek Forty Series: IS42mm Top / IS52mm Bottom Tapered |
| BRAKE LEVERS | Shimano XT |
| BRAKES | Shimano XT Hydraulic Disc 180/160mm |
| CASSETTE | Sram XG-1195 10-42T 11spd |
| CHAIN | Sram PC-XX1 11spd |
| CRANKS | Race Face Next SL 170-175mm DM32 1x11spd |
| BOTTOM BRACKET | Race Face Cinch 30mm BB92 Pressfit |
| SHIFTERS | Sram X01 Trigger 1x11spd |
| F. DERAILLEUR | N/A |
| R. DERAILLEUR | Sram X01 Type 2 All Mountain 11spd |
| F. HUB | Stan's 3.30 Disc / 15mm Axle |
| R. HUB | Stan's 3.30 Disc / 6 Pawl Freehub / 142 x 12mm Axle |
| SPOKES | DT Swiss Competition / Alloy Nipples |
| RIMS | Stan's ZTR Crest Tubeless Ready |
| TIRES | Maxxis Ikon Maxx Speed Tubeless Ready 29" x 2.2" |
| HANDELBAR | Race Face Next Carbon 1/2 Rise Ø35mm x 740mm x 9° Sweep |
| STEM | Race Face Turbine CNC 35mm 6° x 70-90mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Silverado SLT Titanium |
| SEATPOST | Race Face Next SL 27.2mm x 400mm |

*Price, specification and availability subject to change without notice.



VERTEX 970 RSL

CRR518



TECHNOLOGY



IMPROVEMENTS

SunRINGLÉ Helix TR25 Rims: Wider Profile and Tubeless Compatible.

High Performance Maxxis Folding Tubeless Tires.

GEOMETRY

| FRAME SIZE | | SM | MD | LG | XL |
|------------------------------|---------|--------|--------|--------|--------|
| HEAD ANGLE | degrees | 70.25° | 70.25° | 70.25° | 70.25° |
| SEAT ANGLE | degrees | 73° | 73° | 73° | 73° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 394 | 432 | 470 | 508 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 570 | 592 | 615 | 638 |
| HEAD TUBE LENGTH | (mm) | 95 | 100 | 115 | 130 |
| CHAINSTAY LENGTH | (mm) | 433 | 433 | 433 | 433 |
| BOTTOM BRACKET DROP | (mm) | 56 | 56 | 56 | 56 |
| STANDOVER HEIGHT | (mm) | 738 | 752 | 776 | 808 |
| WHEELBASE | (mm) | 1065 | 1087 | 1111 | 1134 |
| REACH | (mm) | 384 | 405 | 424 | 442 |
| STACK | (mm) | 607 | 612 | 626 | 640 |

* More details on measurements on demand.

SPECIFICATIONS / SPÉCIFICATIONS

| | |
|----------------|---|
| FRAME | C13 Hi Mod Carbon Smoothwall Monocoque. Tapered Head Tube. Press Fit BB. Internal Cable Routing. |
| COLOR | Matte Blue |
| SIZES | S - M - L - XL |
| FORK | RockShox SID RL 29. 100mm. Motion Control DNA Lockout / Rebound / 15mm Maxle Lite / Tapered Steerer |
| HEADSET | Cane Creek Fifteen Series: IS42mm Top / IS52mm Bottom Tapered |
| BRAKE LEVERS | Shimano XT I-Spec Shifter Mount |
| BRAKES | Shimano XT Hydraulic Disc 180/160mm |
| CASSETTE | Shimano HG81 11-36T 10spd |
| CHAIN | Shimano HG95 10spd |
| CRANKS | Race Face Turbine 170-175mm 38/24T 2x10spd |
| BOTTOM BRACKET | Race Face Press Fit Team XC |
| SHIFTERS | Shimano XT Rapid Fire I-Spec 2x10spd |
| F. DERAILLEUR | Shimano XT 34.9mm 2x10spd |
| R. DERAILLEUR | Shimano XTR Direct Mount 10spd |
| F. HUB | Shimano XT / Centerlock / 32H / 15mm Axle |
| R. HUB | Shimano XT / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Champion |
| RIMS | Wheeltech Helix TR25 Tubeless Compatible by SUNringlé |
| TIRES | Maxxis Ikon Maxx Speed Tubeless Ready 29" x 2.2" |
| HANDELBAR | Race Face Turbine Flat Wide Ø31.8mm x 720mm x 9° Sweep |
| STEM | Race Face Turbine 6° x 70-100mm |
| GRIPS | Rocky Mountain Lock On XC |
| SADDLE | WTB Silverado Race |
| SEATPOST | Rocky Mountain SL 27.2 x 400mm |

*Price, specification and availability subject to change without notice.



VERTEX 950 RSL

CRR517



TECHNOLOGY



IMPROVEMENTS

Manitou Marvel Pro: High Performance Absolute + TPC Damper.

Shimano XT Shifters, Brakes and Front Derailleur.

High Performance Maxxis Folding Tires.

GEOMETRY

| FRAME SIZE | | SM | MD | LG | XL |
|------------------------------|---------|--------|--------|--------|--------|
| HEAD ANGLE | degrees | 70.25° | 70.25° | 70.25° | 70.25° |
| SEAT ANGLE | degrees | 73° | 73° | 73° | 73° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 394 | 432 | 470 | 508 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 570 | 592 | 615 | 638 |
| HEAD TUBE LENGTH | (mm) | 95 | 100 | 115 | 130 |
| CHAINSTAY LENGTH | (mm) | 433 | 433 | 433 | 433 |
| BOTTOM BRACKET DROP | (mm) | 56 | 56 | 56 | 56 |
| STANDOVER HEIGHT | (mm) | 738 | 752 | 776 | 808 |
| WHEELBASE | (mm) | 1065 | 1087 | 1111 | 1134 |
| REACH | (mm) | 384 | 405 | 424 | 442 |
| STACK | (mm) | 607 | 612 | 626 | 640 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | C13 Hi Mod Carbon Smoothwall Monocoque. Tapered Head Tube. Press Fit BB. Internal Cable Routing. |
| COLOR | Matte Carbon |
| SIZES | S - M - L - XL |
| FORK | Manitou Marvel Pro. 100mm. TPC Absolute+ Damper / Compression / Lockout / Rebound / 15mm HexLock Axle / Tapered Steerer |
| HEADSET | Cane Creek Fifteen Series: 1542mm Top / 52mm Bottom Tapered |
| BRAKE LEVERS | Shimano XT I-Spec Shifter Mount |
| BRAKES | Shimano XT Hydraulic Disc 180/160mm |
| CASSETTE | Shimano HG81 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | Race Face Evolve 170-175mm 38/24T 2x10spd |
| BOTTOM BRACKET | Race Face Press Fit Team XC |
| SHIFTERS | Shimano XT Rapid Fire I- Spec 2x10spd |
| F. DERAILLEUR | Shimano XT 34.9mm 2x10spd |
| R. DERAILLEUR | Shimano XT Direct Mount 10spd |
| F. HUB | Shimano 618 / Centerlock / 32H / 15mm Axle |
| R. HUB | Shimano 618 / Centerlock / 32H / 12 x 142mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | Wheeltech Inferno 23 by SUNringlé |
| TIRES | Maxxis Ikon Maxx Speed Tubeless Ready 29" x 2.2" |
| HANDELBAR | Rocky Mountain Zero9 Flat Ø31.8mm x 700mm x 9° Sweep |
| STEM | Rocky Mountain L7 7° x 70-100mm |
| GRIPS | Rocky Mountain XC kraton |
| SADDLE | WTB Volt Race |
| SEATPOST | Rocky Mountain SL 27.2 x 400mm |

*Price, specification and availability subject to change without notice.



VERTEX 950

CRR515



TECHNOLOGY



IMPROVEMENTS

Manitou Marvel Pro: High Performance Absolute + TPC Damper.

Shimano XT Shifters, Brakes and Front Derailleur.

Shimano MT15 Wheelset for Light Weight.

GEOMETRY

| FRAME SIZE | | XS** | SM | MD | LG | XL |
|------------------------------|---------|-------|--------|--------|--------|--------|
| HEAD ANGLE | degrees | 69.5° | 70.25° | 70.25° | 70.25° | 70.25° |
| SEAT ANGLE | degrees | 74° | 73° | 73° | 73° | 73° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 355 | 394 | 432 | 470 | 508 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 550 | 570 | 592 | 615 | 638 |
| HEAD TUBE LENGTH | (mm) | 100 | 105 | 110 | 115 | 130 |
| CHAINSTAY LENGTH | (mm) | 435 | 435 | 435 | 435 | 435 |
| BOTTOM BRACKET DROP | (mm) | 56 | 56 | 56 | 56 | 56 |
| STANDOVER HEIGHT | (mm) | 719 | 738 | 752 | 776 | 808 |
| WHEELBASE | (mm) | 1068 | 1065 | 1087 | 1111 | 1134 |
| REACH | (mm) | 381 | 384 | 405 | 424 | 442 |
| STACK | (mm) | 587 | 607 | 612 | 626 | 640 |

* More details on measurements on demand / ** 80mm travel fork

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | Rocky Mountain FORM™ Series Custom Hydroformed Alloy. Press Fit BB. Zero Stack Tapered Headtube Internal Cable Routing |
| COLOR | Matte Green |
| SIZES | XS - S - M - L - XL |
| FORK | Manitou Marvel Pro. 100mm (XS: 80mm). TPC Absolute+ Damper / Compression / Lockout / Rebound / 15mm HexLock Axle / Tapered Steerer |
| HEADSET | Cane Creek Fifteen Series: Z544mm Top / Z556mm Bottom Tapered |
| BRAKE LEVERS | Shimano XT I-Spec Shifter Mount |
| BRAKES | Shimano XT Hydraulic Disc 180/160mm |
| CASSETTE | Shimano HG81 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | Race Face Evolve 170-175mm 38/24T 2x10spd |
| BOTTOM BRACKET | Race Face Press Fit Team XC |
| SHIFTERS | Shimano XT Rapid Fire I- Spec 2x10spd |
| F. DERAILLEUR | Shimano XT 31.8mm 2x10spd |
| R. DERAILLEUR | Shimano XT 10spd |
| F. HUB | Shimano MT15 / Centerlock / 28H / 15mm Axle |
| R. HUB | Shimano MT15 / Centerlock / 28H / 10 x 135mm QR |
| SPOKES | Shimano Stainless |
| RIMS | Shimano MT15 |
| TIRES | Maxxis Ikon Maxx Speed Tubeless Ready 29" x 2.2" |
| HANDELBAR | Race Face Ride Flat Wide Ø31.8mm x 710mm x 9° Sweep |
| STEM | Rocky Mountain L7 7° x 70-100mm |
| GRIPS | Rocky Mountain XC Kraton |
| SADDLE | WTB Volt Race |
| SEATPOST | Rocky Mountain SL 27.2 x 400mm |

*Price, specification and availability subject to change without notice.



VERTEX 930

CRR512



TECHNOLOGY



IMPROVEMENTS

High Performance Maxxis Folding Tires.

Comfortable WTB Volt Saddle.

GEOMETRY

| FRAME SIZE | | XS** | SM | MD | LG | XL |
|------------------------------|---------|-------|--------|--------|--------|--------|
| HEAD ANGLE | degrees | 69.5° | 70.25° | 70.25° | 70.25° | 70.25° |
| SEAT ANGLE | degrees | 74° | 73° | 73° | 73° | 73° |
| SEAT TUBE (CENTER BB TO TOP) | (mm) | 355 | 394 | 432 | 470 | 508 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 550 | 570 | 592 | 615 | 638 |
| HEAD TUBE LENGTH | (mm) | 100 | 105 | 110 | 115 | 130 |
| CHAINSTAY LENGTH | (mm) | 435 | 435 | 435 | 435 | 435 |
| BOTTOM BRACKET DROP | (mm) | 56 | 56 | 56 | 56 | 56 |
| STANDOVER HEIGHT | (mm) | 719 | 738 | 752 | 776 | 808 |
| WHEELBASE | (mm) | 1068 | 1065 | 1087 | 1111 | 1134 |
| REACH | (mm) | 381 | 384 | 405 | 424 | 442 |
| STACK | (mm) | 587 | 607 | 612 | 626 | 640 |

* More details on measurements on demand /** 80mm travel fork

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | Rocky Mountain FORM™ Series Custom Hydroformed Alloy. Press Fit BB. Zero Stack Tapered Headtube Internal Cable Routing |
| COLOR | Gloss Blue |
| SIZES | XS - S - M - L - XL |
| FORK | Manitou Marvel Comp TS Air. 100mm (XS: 80mm). Compression / Lockout / Rebound / Tapered Steerer |
| HEADSET | Cane Creek Fifteen Series: Z544mm Top / Z556mm Bottom Tapered |
| BRAKE LEVERS | Shimano BL-M446 |
| BRAKES | Shimano BR-M446 Hydraulic Disc 180/160mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | Shimano M552 170-175mm 42/32/24T 10spd |
| BOTTOM BRACKET | Shimano SMBB71 Press Fit |
| SHIFTERS | Shimano Deore Rapid Fire 10spd |
| F. DERAILLEUR | Shimano Deore 31.8mm 10spd |
| R. DERAILLEUR | Shimano XT 10spd |
| F. HUB | Shimano RM66 / Centerlock / 32H |
| R. HUB | Shimano RM66 / Centerlock / 32H |
| SPOKES | Stainless |
| RIMS | Wheeltech TD26 by Alex Rims |
| TIRES | Maxxis Ikon Folding 29" x 2.2" |
| HANDELBAR | Rocky Mountain Zero9 Flat Ø31.8mm x 700mm x 9° Sweep |
| STEM | Rocky Mountain L7 7° x 70-100mm |
| GRIPS | Rocky Mountain XC Kraton |
| SADDLE | WTB Volt |
| SEATPOST | Rocky Mountain SL 27.2 x 400mm |

*Price, specification and availability subject to change without notice.



BLIZZARD (XT / SLX)

CRW500



CFW500

- Frame
- RockShox Bluto RL fork
- Wheeltech Fatso Hubs

* Image for reference only
**integrated bag optional

TECHNOLOGY



GEOMETRY

| FRAME SIZE | | S | M | L | XL |
|------------------------------|---------|------|------|------|------|
| HEAD ANGLE | degrees | 68.5 | 68.5 | 68.5 | 68.5 |
| SEAT ANGLE | degrees | 73.5 | 73.5 | 73.5 | 73.5 |
| SEAT TUBE (CENTRE BB TO TOP) | (mm) | 430 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 570 | 590 | 610 | 635 |
| HEAD TUBE LENGTH | (mm) | 115 | 115 | 120 | 140 |
| CHAINSTAY LENGTH | (mm) | 455 | 455 | 455 | 455 |
| BOTTOM BRACKET DROP | (mm) | 52 | 52 | 52 | 52 |
| FORK RAKE | (mm) | 51 | 51 | 51 | 51 |
| WHEELBASE | (mm) | 1118 | 1138 | 1160 | 1185 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------------|---|
| FRAME | Rocky Mountain FORM™ Series Custom Hydroformed Alloy. 100mm BB. 12x197mm Axle. Zero Stack Tapered Headtube Internal Cable Routing. Reverb Stealth Compatible. |
| COLOR | Matte Black |
| SIZES | S - M - L - XL |
| FORK | RockShox Bluto RL. 100mm. Motion Control DNA Lockout / Rebound / 15x150mm Maxle Lite / Tapered Steerer |
| HEADSET | Cane Creek Fifteen Series: ZS44mm Top / ZS56mm Bottom Tapered |
| BRAKE LEVERS | Shimano SLX I-Spec Shifter Mount |
| BRAKES | Shimano SLX Hydraulic Disc 180/160mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | KMC X10 10spd EcoProtect Anti Rust |
| CRANKS | Race Face 170-175mm Bash/24T 1x10spd |
| BOTTOM BRACKET | Race Face 100mm Team XC |
| SHIFTERS | Shimano SLX Rapid Fire 1x10spd |
| F. DERAILLEUR | N/A |
| R. DERAILLEUR | Shimano XT Shadow Plus 10spd |
| F. HUB | Wheeltech Fatso Hub / 6 Bolt / 32H / 15x150mm Axle |
| R. HUB | Wheeltech Fatso Hub / 6 Bolt / 32H / 6 Pawl Freehub Body / 12x197mm Axle |
| SPOKES | DT Swiss Competition |
| RIMS | SUNRingle Mulefüt 80 Tubeless Compatible |
| TIRES | Vee Rubber Bulldozer Folding 26" x 4.7" |
| HANDELBAR | Race Face Flat Wide Ø31.8mm x 710mm x 9° Sweep |
| STEM | Rocky Mountain L7 7° x 60-70mm |
| GRIPS | Rocky Mountain XC Kraton |
| SADDLE | WTB Volt Race |
| SEATPOST | Rocky Mountain SL 30.9 x 400mm |
| OPTIONAL ACCESSORIES | Porcelain Rocket Integrated 1/2 Frame Pack |

*Price, specification and availability subject to change without notice.



BLIZZARD (DEORE)

CRW503



* Image for reference only
**integrated bag optional

TECHNOLOGY



GEOMETRY

| FRAME SIZE | | S | M | L | XL |
|------------------------------|---------|------|------|------|------|
| HEAD ANGLE | degrees | 68.5 | 68.5 | 68.5 | 68.5 |
| SEAT ANGLE | degrees | 73.5 | 73.5 | 73.5 | 73.5 |
| SEAT TUBE (CENTRE BB TO TOP) | (mm) | 430 | 457 | 483 | 521 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 570 | 590 | 610 | 635 |
| HEAD TUBE LENGTH | (mm) | 115 | 115 | 120 | 140 |
| CHAINSTAY LENGTH | (mm) | 455 | 455 | 455 | 455 |
| BOTTOM BRACKET DROP | (mm) | 52 | 52 | 52 | 52 |
| FORK RAKE | (mm) | 51 | 51 | 51 | 51 |
| WHEELBASE | (mm) | 1118 | 1138 | 1160 | 1185 |

* More details on measurements on demand.

SPECIFICATIONS

| | |
|----------------------|---|
| FRAME | Rocky Mountain FORM™ Series Custom Hydroformed Alloy. 100mm BB. 12x197mm Axle. Zero Stack Tapered Headtube Internal Cable Routing. Reverb Stealth Compatible. |
| COLOR | Matte Black |
| SIZES | S - M - L - XL |
| FORK | Rocky Mountain Fat Al. Suspension Corrected. 15x 150mm Maxle Lite / Tapered Steerer |
| HEADSET | PSA No. 57B: Z544mm Top / Z556mm Bottom Tapered |
| BRAKE LEVERS | Shimano M446 |
| BRAKES | Shimano M446 Hydraulic Disc 180/160mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | KMC X10 10spd EcoProtect Anti Rust |
| CRANKS | Race Face 170-175mm Bash/24T 1x10spd |
| BOTTOM BRACKET | Race Face 100mm Team XC |
| SHIFTERS | Shimano Deore Rapid Fire 1x10spd |
| F. DERAILLEUR | N/A |
| R. DERAILLEUR | Shimano Deore Shadow Plus 10spd |
| F. HUB | Wheeltech Fatso Hub / 6 Bolt / 32H / 15x150mm Axle |
| R. HUB | Wheeltech Fatso Hub / 6 Bolt / 32H / 12x197mm Axle |
| SPOKES | DT Swiss Champion |
| RIMS | SUNringlé Mulefüt 80 Tubeless Compatible |
| TIRES | Vee Rubber Bulldozer Folding 26" x 4.7" |
| HANDELBAR | Rocky Mountain Zero9 Flat Ø31.8mm x 700mm x 9° Sweep |
| STEM | Rocky Mountain XC7 7° x 60-70mm |
| GRIPS | Rocky Mountain XC Kraton |
| SADDLE | WTB Volt |
| SEATPOST | Rocky Mountain SL 30.9 x 400mm |
| OPTIONAL ACCESSORIES | Porcelain Rocket Integrated 1/2 Frame Pack |

*Price, specification and availability subject to change without notice.



TRAILHEAD 29

CRR509 - COLOR 1



TECHNOLOGY



IMPROVEMENTS

Tapered Headtube for Increased Steering Response.

High Performance Schwalbe Tires.

Comfortable WTB Volt Saddle.

GEOMETRY

| FRAME SIZE | | XS** | SM | MD | LG | XL |
|------------------------------|---------|-------|--------|--------|--------|--------|
| HEAD ANGLE | degrees | 69.5° | 70.25° | 70.25° | 70.25° | 70.25° |
| SEAT ANGLE | degrees | 74° | 73° | 73° | 73° | 73° |
| SEAT TUBE (CENTRE BB TO TOP) | (mm) | 355 | 394 | 432 | 470 | 508 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 550 | 570 | 592 | 615 | 638 |
| HEAD TUBE LENGTH | (mm) | 100 | 100 | 100 | 115 | 130 |
| CHAINSTAY LENGTH | (mm) | 447 | 447 | 447 | 447 | 447 |
| BOTTOM BRACKET DROP | (mm) | 56 | 56 | 56 | 56 | 56 |
| STANDOVER HEIGHT | (mm) | 719 | 738 | 752 | 776 | 808 |
| WHEELBASE | (mm) | 1078 | 1071 | 1093 | 1117 | 1140 |

* More details on measurements on demand / ** 80mm travel fork

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | Rocky Mountain 6061 Series Custom Hydroformed Alloy. Threaded BB. Tapered Zerostack Headtube. Rack and Fender Mounts. |
| COLOR | Matte Green |
| SIZES | XS - S - M - L - XL |
| FORK | RockShox XC32 TK 29 Solo Air. 100mm (XS: 80mm). Turnkey Lockout / Rebound |
| HEADSET | FSA #57 Internal: Z544 Z556mm |
| BRAKE LEVERS | Shimano BL-M446 |
| BRAKES | Shimano BR-M446 Hydraulic Disc 160mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | Shimano Deore 170-175mm 42/32/24T 10spd |
| BOTTOM BRACKET | Shimano Deore Hollowtech |
| SHIFTERS | Shimano Deore Rapid Fire 10spd |
| F. DERAILLEUR | Shimano Deore 31.8mm 10spd |
| R. DERAILLEUR | Shimano SLX Shadow 10spd |
| F. HUB | Shimano RM66 / Centerlock / 32H |
| R. HUB | Shimano RM66 / Centerlock / 32H |
| SPOKES | Stainless |
| RIMS | Wheeltech SX19 By WTB |
| TIRES | Schwalbe Rapid Rob 29" x 2.1" |
| HANDELBAR | Rocky Mountain Zero9 Flat Ø31.8mm x 700mm x 9° Sweep |
| STEM | Rocky Mountain L7 7° x 60-90mm |
| GRIPS | Rocky Mountain XC Kraton |
| SADDLE | WTB Volt |
| SEATPOST | Rocky Mountain L2B 27.2mm x 400mm |

*Price, specification and availability subject to change without notice.



TRAILHEAD 29

CRR509 - COLOR 2



TECHNOLOGY



IMPROVEMENTS

Tapered Headtube for Increased Steering Response.

High Performance Schwalbe Tires.

Comfortable WTB Volt Saddle.

GEOMETRY

| FRAME SIZE | | XS** | SM | MD | LG | XL |
|------------------------------|---------|-------|--------|--------|--------|--------|
| HEAD ANGLE | degrees | 69.5° | 70.25° | 70.25° | 70.25° | 70.25° |
| SEAT ANGLE | degrees | 74° | 73° | 73° | 73° | 73° |
| SEAT TUBE (CENTRE BB TO TOP) | (mm) | 355 | 394 | 432 | 470 | 508 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 550 | 570 | 592 | 615 | 638 |
| HEAD TUBE LENGTH | (mm) | 100 | 100 | 100 | 115 | 130 |
| CHAINSTAY LENGTH | (mm) | 447 | 447 | 447 | 447 | 447 |
| BOTTOM BRACKET DROP | (mm) | 56 | 56 | 56 | 56 | 56 |
| STANDOVER HEIGHT | (mm) | 719 | 738 | 752 | 776 | 808 |
| WHEELBASE | (mm) | 1078 | 1071 | 1093 | 1117 | 1140 |

* More details on measurements on demand /** 80mm travel fork

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | Rocky Mountain 6061 Series Custom Hydroformed Alloy. Threaded BB. Tapered Zerostack Headtube. Rack and Fender Mounts. |
| COLOR | Matte Black |
| SIZES | XS - S - M - L - XL |
| FORK | RockShox XC32 TK 29 Solo Air. 100mm (XS: 80mm). Turnkey Lockout / Rebound |
| HEADSET | FSA #57 Internal: Z544 Z556mm |
| BRAKE LEVERS | Shimano BL-M446 |
| BRAKES | Shimano BR-M446 Hydraulic Disc 160mm |
| CASSETTE | Shimano HG50 11-36T 10spd |
| CHAIN | Shimano HG54 10spd |
| CRANKS | Shimano Deore 170-175mm 42/32/24T 10spd |
| BOTTOM BRACKET | Shimano Deore Hollowtech |
| SHIFTERS | Shimano Deore Rapid Fire 10spd |
| F. DERAILLEUR | Shimano Deore 31.8mm 10spd |
| R. DERAILLEUR | Shimano SLX Shadow 10spd |
| F. HUB | Shimano RM66 / Centerlock / 32H |
| R. HUB | Shimano RM66 / Centerlock / 32H |
| SPOKES | Stainless |
| RIMS | Wheeltech SX19 By WTB |
| TIRES | Schwalbe Rapid Rob 29" x 2.1" |
| HANDELBAR | Rocky Mountain Zero9 Flat Ø31.8mm x 700mm x 9° Sweep |
| STEM | Rocky Mountain L7 7° x 60-90mm |
| GRIPS | Rocky Mountain XC Kraton |
| SADDLE | WTB Volt |
| SEATPOST | Rocky Mountain L2B 27.2mm x 400mm |

*Price, specification and availability subject to change without notice.



FUSION 29

CRR508 - COLOR 1



TECHNOLOGY



IMPROVEMENTS

Tapered Headtube for Increased Steering Response.

High Performance Maxxis Tires.

Comfortable WTb Volt Saddle.

GEOMETRY

| FRAME SIZE | | XS** | SM | MD | LG | XL |
|------------------------------|---------|-------|--------|--------|--------|--------|
| HEAD ANGLE | degrees | 69.5° | 70.25° | 70.25° | 70.25° | 70.25° |
| SEAT ANGLE | degrees | 74° | 73° | 73° | 73° | 73° |
| SEAT TUBE (CENTRE BB TO TOP) | (mm) | 355 | 394 | 432 | 470 | 508 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 550 | 570 | 592 | 615 | 638 |
| HEAD TUBE LENGTH | (mm) | 100 | 100 | 100 | 115 | 130 |
| CHAINSTAY LENGTH | (mm) | 447 | 447 | 447 | 447 | 447 |
| BOTTOM BRACKET DROP | (mm) | 56 | 56 | 56 | 56 | 56 |
| STANDOVER HEIGHT | (mm) | 719 | 738 | 752 | 776 | 808 |
| WHEELBASE | (mm) | 1078 | 1071 | 1093 | 1117 | 1140 |

* More details on measurements on demand / ** 80mm travel fork

SPECIFICATIONS

| | |
|----------------|--|
| FRAME | Rocky Mountain 6061 Series Custom Hydroformed Alloy. Threaded BB. Tapered Zerostack Headtube. Rack and Fender Mounts.. |
| COLOR | Matte Blue |
| SIZES | XS - S - M - L - XL |
| FORK | RockShox XC30 TK 29, 100mm (XS: 80mm), Turnkey Lockout / Rebound |
| HEADSET | FSA #57 Internal: Z544 Z556mm |
| BRAKE LEVERS | Shimano BL-M446 |
| BRAKES | Shimano BR-M446 Hydraulic Disc 160mm |
| CASSETTE | Shimano HG200 11-34 9spd |
| CHAIN | Shimano HG53 9spd |
| CRANKS | Shimano Deore 170-175mm 44/32/22T 9spd |
| BOTTOM BRACKET | Shimano Deore Hollowtech |
| SHIFTERS | Shimano Alivio Rapid Fire 9spd |
| F. DERAILLEUR | Shimano Acera 31.8mm 9spd |
| R. DERAILLEUR | Shimano Deore Shadow 9spd |
| F. HUB | Shimano RM35 / Centerlock / 32H |
| R. HUB | Shimano RM35 / Centerlock / 32H |
| SPOKES | Stainless |
| RIMS | Wheeltech SX19 By WTb |
| TIRES | Maxxis Ikon 29" x 2.2" |
| HANDELBAR | Rocky Mountain Zero9 Flat Ø31.8mm x 700mm x 9° Sweep |
| STEM | Rocky Mountain XC7 7° x 60-90mm |
| GRIPS | Rocky Mountain XC Kraton |
| SADDLE | WTb Volt |
| SEATPOST | Rocky Mountain L2B 27.2mm x 400mm |

*Price, specification and availability subject to change without notice.



FUSION 29

CRR508 - COLOR 2



TECHNOLOGY



IMPROVEMENTS

Tapered Headtube for Increased Steering Response.

High Performance Maxxis Tires.

Comfortable WTb Volt Saddle.

GEOMETRY

| FRAME SIZE | | XS** | SM | MD | LG | XL |
|------------------------------|---------|-------|--------|--------|--------|--------|
| HEAD ANGLE | degrees | 69.5° | 70.25° | 70.25° | 70.25° | 70.25° |
| SEAT ANGLE | degrees | 74° | 73° | 73° | 73° | 73° |
| SEAT TUBE (CENTRE BB TO TOP) | (mm) | 355 | 394 | 432 | 470 | 508 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 550 | 570 | 592 | 615 | 638 |
| HEAD TUBE LENGTH | (mm) | 100 | 100 | 100 | 115 | 130 |
| CHAINSTAY LENGTH | (mm) | 447 | 447 | 447 | 447 | 447 |
| BOTTOM BRACKET DROP | (mm) | 56 | 56 | 56 | 56 | 56 |
| STANDOVER HEIGHT | (mm) | 719 | 738 | 752 | 776 | 808 |
| WHEELBASE | (mm) | 1078 | 1071 | 1093 | 1117 | 1140 |

* More details on measurements on demand / ** 80mm travel fork

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | Rocky Mountain 6061 Series Custom Hydroformed Alloy. Threaded BB. Tapered Zerostack Headtube. Rack and Fender Mounts. |
| COLOR | Matte Black |
| SIZES | XS - S - M - L - XL |
| FORK | RockShox XC30 TK 29, 100mm (XS: 80mm), Turnkey Lockout / Rebound |
| HEADSET | FSA #57 Internal: Z544 Z556mm |
| BRAKE LEVERS | Shimano BL-M446 |
| BRAKES | Shimano BR-M446 Hydraulic Disc 160mm |
| CASSETTE | Shimano HG200 11-34 9spd |
| CHAIN | Shimano HG53 9spd |
| CRANKS | Shimano Deore 170-175mm 44/32/22T 9spd |
| BOTTOM BRACKET | Shimano Deore Hollowtech |
| SHIFTERS | Shimano Alivio Rapid Fire 9spd |
| F. DERAILLEUR | Shimano Acera 31.8mm 9spd |
| R. DERAILLEUR | Shimano Deore Shadow 9spd |
| F. HUB | Shimano RM35 / Centerlock / 32H |
| R. HUB | Shimano RM35 / Centerlock / 32H |
| SPOKES | Stainless |
| RIMS | Wheeltech SX19 By WTb |
| TIRES | Maxxis Ikon 29" x 2.2" |
| HANDELBAR | Rocky Mountain Zero9 Flat Ø31.8mm x 700mm x 9° Sweep |
| STEM | Rocky Mountain XC7 7° x 60-90mm |
| GRIPS | Rocky Mountain XC Kraton |
| SADDLE | WTb Volt |
| SEATPOST | Rocky Mountain L2B 27.2mm x 400mm |

*Price, specification and availability subject to change without notice.



SOUL 29

CRR506 - COLOR 1



TECHNOLOGY



IMPROVEMENTS

Tapered Headtube for Increased Steering Response.

High Performance Maxxis Tires.

Comfortable WTB Volt Saddle.

GEOMETRY

| FRAME SIZE | | XS** | SM | MD | LG | XL |
|------------------------------|---------|-------|--------|--------|--------|--------|
| HEAD ANGLE | degrees | 69.5° | 70.25° | 70.25° | 70.25° | 70.25° |
| SEAT ANGLE | degrees | 74° | 73° | 73° | 73° | 73° |
| SEAT TUBE (CENTRE BB TO TOP) | (mm) | 355 | 394 | 432 | 470 | 508 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 550 | 570 | 592 | 615 | 638 |
| HEAD TUBE LENGTH | (mm) | 100 | 100 | 100 | 115 | 130 |
| CHAINSTAY LENGTH | (mm) | 447 | 447 | 447 | 447 | 447 |
| BOTTOM BRACKET DROP | (mm) | 56 | 56 | 56 | 56 | 56 |
| STANDOVER HEIGHT | (mm) | 719 | 738 | 752 | 776 | 808 |
| WHEELBASE | (mm) | 1078 | 1071 | 1093 | 1117 | 1140 |

* More details on measurements on demand /** 80mm travel fork

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | Rocky Mountain 6061 Series Custom Hydroformed Alloy. Threaded BB. Tapered Zerostack Headtube. Rack and Fender Mounts. |
| COLOR | Matte Orange |
| SIZES | XS - S - M - L - XL |
| FORK | RockShox XC28 TK 29, 100mm (XS: 80mm), Turnkey Lockout / Rebound |
| HEADSET | FSA #57 Internal: Z544 Z556mm |
| BRAKE LEVERS | Shimano BL-M355 |
| BRAKES | Shimano BR-M355 Hydraulic Disc 160mm |
| CASSETTE | Shimano HG200 11-34 9spd |
| CHAIN | Shimano HG53 9spd |
| CRANKS | Shimano M391 170-175mm 42/32/22T |
| BOTTOM BRACKET | FSA 7420 |
| SHIFTERS | Shimano Acera Rapid Fire 9spd |
| F. DERAILLEUR | Shimano Acera 9spd 31.8mm |
| R. DERAILLEUR | Shimano Alivio 9spd |
| F. HUB | Shimano RM35 / Centerlock / 32H |
| R. HUB | Shimano RM35 / Centerlock / 32H |
| SPOKES | Stainless |
| RIMS | Wheeltech TD26 By Alex |
| TIRES | Maxxis Sphinx 29" x 2.1" |
| HANDELBAR | Rocky Mountain Zero6 Flat Ø31.8mm x 670mm x 6° Sweep |
| STEM | Rocky Mountain XC7 7° x 60-90mm |
| GRIPS | Rocky Mountain XC Kraton |
| SADDLE | WTB Volt |
| SEATPOST | Rocky Mountain XC 27.2mm x 400mm |

*Price, specification and availability subject to change without notice.



SOUL 29

CRR506 - COLOR 2



TECHNOLOGY



IMPROVEMENTS

Tapered Headtube for Increased Steering Response.

High Performance Maxxis Tires.

Comfortable WTB Volt Saddle.

GEOMETRY

| FRAME SIZE | | XS** | SM | MD | LG | XL |
|------------------------------|---------|-------|--------|--------|--------|--------|
| HEAD ANGLE | degrees | 69.5° | 70.25° | 70.25° | 70.25° | 70.25° |
| SEAT ANGLE | degrees | 74° | 73° | 73° | 73° | 73° |
| SEAT TUBE (CENTRE BB TO TOP) | (mm) | 355 | 394 | 432 | 470 | 508 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 550 | 570 | 592 | 615 | 638 |
| HEAD TUBE LENGTH | (mm) | 100 | 100 | 100 | 115 | 130 |
| CHAINSTAY LENGTH | (mm) | 447 | 447 | 447 | 447 | 447 |
| BOTTOM BRACKET DROP | (mm) | 56 | 56 | 56 | 56 | 56 |
| STANDOVER HEIGHT | (mm) | 719 | 738 | 752 | 776 | 808 |
| WHEELBASE | (mm) | 1078 | 1071 | 1093 | 1117 | 1140 |

* More details on measurements on demand /** 80mm travel fork

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | Rocky Mountain 6061 Series Custom Hydroformed Alloy. Threaded BB. Tapered Zerostack Headtube. Rack and Fender Mounts. |
| COLOR | Matte Black |
| SIZES | XS - S - M - L - XL |
| FORK | RockShox XC28 TK 29. 100mm (XS: 80mm), Turnkey Lockout / Rebound |
| HEADSET | FSA #57 Internal: Z544 Z556mm |
| BRAKE LEVERS | Shimano BL-M355 |
| BRAKES | Shimano BR-M355 Hydraulic Disc 160mm |
| CASSETTE | Shimano HG200 11-34 9spd |
| CHAIN | Shimano HG53 9spd |
| CRANKS | Shimano M391 170-175mm 42/32/22T |
| BOTTOM BRACKET | FSA 7420 |
| SHIFTERS | Shimano Acera Rapid Fire 9spd |
| F. DERAILLEUR | Shimano Acera 9spd 31.8mm |
| R. DERAILLEUR | Shimano Alivio 9spd |
| F. HUB | Shimano RM35 / Centerlock / 32H |
| R. HUB | Shimano RM35 / Centerlock / 32H |
| SPOKES | Stainless |
| RIMS | Wheeltech TD26 By Alex |
| TIRES | Maxxis Sphinx 29" x 2.1" |
| HANDELBAR | Rocky Mountain Zero6 Flat Ø31.8mm x 670mm x 6° Sweep |
| STEM | Rocky Mountain XC7 7° x 60-90mm |
| GRIPS | Rocky Mountain XC Kraton |
| SADDLE | WTB Volt |
| SEATPOST | Rocky Mountain XC 27.2mm x 400mm |

*Price, specification and availability subject to change without notice.



FLARE 29

CRR503 - COLOR 1



TECHNOLOGY



IMPROVEMENTS

Tapered Headtube for Increased Steering Response.

High Performance Maxxis Tires.

Comfortable WTB Volt Saddle.

GEOMETRY

| FRAME SIZE | | XS** | SM | MD | LG | XL |
|------------------------------|---------|-------|--------|--------|--------|--------|
| HEAD ANGLE | degrees | 69.5° | 70.25° | 70.25° | 70.25° | 70.25° |
| SEAT ANGLE | degrees | 74° | 73° | 73° | 73° | 73° |
| SEAT TUBE (CENTRE BB TO TOP) | (mm) | 355 | 394 | 432 | 470 | 508 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 550 | 570 | 592 | 615 | 638 |
| HEAD TUBE LENGTH | (mm) | 100 | 100 | 100 | 115 | 130 |
| CHAINSTAY LENGTH | (mm) | 447 | 447 | 447 | 447 | 447 |
| BOTTOM BRACKET DROP | (mm) | 56 | 56 | 56 | 56 | 56 |
| STANDOVER HEIGHT | (mm) | 719 | 738 | 752 | 776 | 808 |
| WHEELBASE | (mm) | 1078 | 1071 | 1093 | 1117 | 1140 |

* More details on measurements on demand / ** 80mm travel fork

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | Rocky Mountain 6061 Series Custom Hydroformed Alloy. Threaded BB. Tapered Zerostack Headtube. Rack and Fender Mounts. |
| COLOR | Matte Black |
| SIZES | XS - S - M - L - XL |
| FORK | Suntour XCT 29. 100mm (XS: 80mm) / Preload |
| HEADSET | FSA #57 Internal: Z544 Z556mm |
| BRAKE LEVERS | Shimano Altus |
| BRAKES | Tektro Novela Mechanical Disc 160mm |
| CASSETTE | Shimano HG200 11-34 9spd |
| CHAIN | Shimano HG53 9spd |
| CRANKS | Suntour XCM V1 170-175mm 44/32/22T 9spd |
| BOTTOM BRACKET | Suntour Sealed Cartridge |
| SHIFTERS | Shimano Altus EZ-Fire 9spd |
| F. DERAILLEUR | Shimano Acera 31.8mm 9spd |
| R. DERAILLEUR | Shimano Alivio 9spd |
| F. HUB | Shimano RM35 / Centerlock / 32H |
| R. HUB | Shimano RM35 / Centerlock / 32H |
| SPOKES | Stainless |
| RIMS | Wheeltech TD26 By Alex |
| TIRES | Maxxis Sphinx 29" x 2.1" |
| HANDELBAR | Rocky Mountain Zero6 Flat Ø31.8mm x 670mm x 6° Sweep |
| STEM | Rocky Mountain XC7 7° x 60-90mm |
| GRIPS | Rocky Mountain XC Kraton |
| SADDLE | WTB Volt |
| SEATPOST | Rocky Mountain XC 27.2mm x 400mm |

*Price, specification and availability subject to change without notice.



FLARE 29

CRR503 - COLOR 2



TECHNOLOGY



IMPROVEMENTS

Tapered Headtube for Increased Steering Response.

High Performance Maxxis Tires.

Comfortable WTB Volt Saddle.

GEOMETRY

| FRAME SIZE | | XS** | SM | MD | LG | XL |
|------------------------------|---------|-------|--------|--------|--------|--------|
| HEAD ANGLE | degrees | 69.5° | 70.25° | 70.25° | 70.25° | 70.25° |
| SEAT ANGLE | degrees | 74° | 73° | 73° | 73° | 73° |
| SEAT TUBE (CENTRE BB TO TOP) | (mm) | 355 | 394 | 432 | 470 | 508 |
| HORIZONTAL TOP TUBE LENGTH | (mm) | 550 | 570 | 592 | 615 | 638 |
| HEAD TUBE LENGTH | (mm) | 100 | 100 | 100 | 115 | 130 |
| CHAINSTAY LENGTH | (mm) | 447 | 447 | 447 | 447 | 447 |
| BOTTOM BRACKET DROP | (mm) | 56 | 56 | 56 | 56 | 56 |
| STANDOVER HEIGHT | (mm) | 719 | 738 | 752 | 776 | 808 |
| WHEELBASE | (mm) | 1078 | 1071 | 1093 | 1117 | 1140 |

* More details on measurements on demand / ** 80mm travel fork

SPECIFICATIONS

| | |
|----------------|---|
| FRAME | Rocky Mountain 6061 Series Custom Hydroformed Alloy. Threaded BB. Tapered Zerostack Headtube. Rack and Fender Mounts. |
| COLOR | Neon Red |
| SIZES | XS - S - M - L - XL |
| FORK | Suntour XCT 29. 100mm (XS: 80mm) / Preload |
| HEADSET | FSA #57 Internal: Z544 Z556mm |
| BRAKE LEVERS | Shimano Altus |
| BRAKES | Tektro Novela Mechanical Disc 160mm |
| CASSETTE | Shimano HG200 11-34 9spd |
| CHAIN | Shimano HG53 9spd |
| CRANKS | Suntour XCM V1 170-175mm 44/32/22T 9spd |
| BOTTOM BRACKET | Suntour Sealed Cartridge |
| SHIFTERS | Shimano Altus EZ-Fire 9spd |
| F. DERAILLEUR | Shimano Acera 31.8mm 9spd |
| R. DERAILLEUR | Shimano Alivio 9spd |
| F. HUB | Shimano RM35 / Centerlock / 32H |
| R. HUB | Shimano RM35 / Centerlock / 32H |
| SPOKES | Stainless |
| RIMS | Wheeltech TD26 By Alex |
| TIRES | Maxxis Sphinx 29" x 2.1" |
| HANDELBAR | Rocky Mountain Zero6 Flat Ø31.8mm x 670mm x 6° Sweep |
| STEM | Rocky Mountain XC7 7° x 60-90mm |
| GRIPS | Rocky Mountain XC Kraton |
| SADDLE | WTB Volt |
| SEATPOST | Rocky Mountain XC 27.2mm x 400mm |

*Price, specification and availability subject to change without notice.